

Ex Control Station CS Box



- Polyamide enclosure system for individual fitting of 22.5 mm control switches (lid mounting or base mounting) and indication devices
- Execution either with 22.5 mm lid holes or without lid holes
- Gland holes M20 / M25 on two sides

Technical data

Approvals

IECEX, ATEX

Explosion protection

Ⓜ II 2 G

Ⓜ II 2 D tD A21

Ex e II T6 (increased safety)

Ex ia IIC T6 (intrinsic safety)

Ex e (ia) IIC T6 (mixed fitting)

Certificates

IECEX PTB 09.0020U, PTB 02 ATEX 1076U,

IECEX PTB 09.0021, PTB 08 ATEX 1109

Temperature range

-20°C to +60°C

Material

Polyamide 12

Colour

RAL 9005, jet black

Ingress protection

IP 66 to EN 60529

Impact resistance

7 Joule to EN 60079-0

Surface resistance

$<10^9$ Ohm to IEC 60093

Ex Control Station CS Box

Product overview

Ex empty enclosure	Ex i terminal enclosure	Ex e terminal enclosure control station	Description	Number of lid holes 22,5 mm	Dimensions H x W x D (mm)
28.10 01 00	58.10 01 00	68.10 01 00	Ex-CS Box 110-0	0	110 x 110 x 85
28.10 01 01	58.10 01 01	68.10 01 01	Ex-CS Box 110-1	1	110 x 110 x 85
28.10 02 00	58.10 02 00	68.10 02 00	Ex-CS Box 160-0	0	110 x 160 x 85
28.10 02 02	58.10 02 02	68.10 02 02	Ex-CS Box 160-2	2	110 x 160 x 85
28.10 02 03	58.10 02 03	68.10 02 03	Ex-CS Box 160-3	3	110 x 160 x 85
28.10 03 00	58.10 03 00	68.10 03 00	Ex-CS Box 230-0	0	110 x 230 x 85
28.10 03 04	58.10 03 04	68.10 03 04	Ex-CS Box 230-4	4	110 x 230 x 85
28.10 03 05	58.10 03 05	68.10 03 05	Ex-CS Box 230-5	5	110 x 230 x 85

Accessories

31.10 99 01	CS Box 110 adapter plate Telemechanique/Technor
31.10 99 02	CS Box 160 adapter plate Telemechanique/Technor
31.10 99 03	CS Box 230 adapter plate Telemechanique/Technor
31.10 99 04	CS Box lid safety strip (set = 2 pcs.)
10.06 14 91	DIN rail TS35/7,5 CS Box 110
10.06 14 92	DIN rail TS35/7,5 CS Box 160
10.06 14 93	DIN rail TS35/7,5 CS Box 230

Technical data see page 19