

# Subracks, individual components

## Horizontal rails




### Z rail for connector IEC 60 603-2 (F)

With 84 x M2.5 thread.

**Material:**  
Extruded aluminium section

**Surface finish:**  
Clear-chromated



Usable width (HP)	Packs of	Model No. RP
4	1	3684.597
8	1	3684.598
20	1	3684.599
40	1	3684.965
42	1	3684.600
63	1	3684.601
84	1	3684.602
84	2	3685.271

### ! Also required:

Assembly screws M2.5 x 6,  
packs of 100, Model No. RP 3654.340,  
see page 576.



### Threaded insert (I)

With M2.5 threaded holes on an HP pitch pattern.  
To slide into the horizontal rail, type A, B, B1, C3,  
C5, D2 and for the rear horizontal rail, reinforced  
version, type C2.

**Material:**  
Sheet steel, zinc-plated

Usable Width (HP)	Packs of	Model No. RP	
		for horizontal rails	
		Front Type A, B, B1, C3, C4, C5, D2	Rear Type C2 Reinforced version
4	1	3684.603	-
8	1	3684.604	-
12	1	3684.605	-
16	1	3684.606	-
20	1	3684.607	-
21	1	3686.149	-
40	1	3684.966	-
42	1	3684.608	3687.616
63	1	3684.609	3687.617
84	1	3684.610	-
84	2	-	3604.830



### Identification strip (J)

To identify the slots on the subrack, self-adhesive.  
The following versions are available.

- 4 mm wide:
  - for horizontal rails
  - for rear horizontal rails
- 2 mm wide:
  - for front horizontal rails (channel on front face)

for horizontal rail	Width mm	Label	Packs of	Model No. RP
Front	4	1 ... 84	1	3687.575
Front	4	1 ... 168	1	3687.577
rear	4	84 ... 1	1	3687.574
Front	2	1 ... 84	1	3687.576



### EMC gaskets, horizontal (K)

see page 507.

3 B 5

Subracks, individual components