

Trim frame

for horizontal mounting kit

To conceal the front sections of the horizontal mounting kit.

Material:

Aluminium, anodised

U horizontal	HP	Model No. RP	
		for 3 U subrack	for 4 U subrack
6	56	3685.783	3685.785
9	84	3685.784	3685.786



Also required:

Collar screws and plastic collars, packs of 100 sets, Model No. RP 3658.160, see page 576.



Trim frame, vented

for horizontal mounting kit

To conceal the front sections of the horizontal mounting kit.

Material:

Aluminium

Surface finish:

Anodised, clear-chromated (EMC version)

Supply includes:

EMC accessories (for EMC version).



U horizontal	HP	Model No. RP	
		for 3 U subrack	for 4 U subrack
6	63	3685.787	3685.788



Also required:

Collar screws and plastic collars, packs of 100 sets, Model No. RP 3658.160, see page 576.


EMC version

U horizontal	HP	Model No. RP	
		for 3 U subrack	for 4 U subrack
6	63	3685.291	3685.292



Also required:

Centering screws, packs of 100, Model No. RP 3687.050, see page 577.



Plastic guide rails

For 160, 220 and 280 mm PCBs up to 2 mm nominal thickness.

2 versions are available:

- Snap-in fastening and screw-fastening
- Snap-in fastening

Material:

Polycarbonate, base material to UL 94-V0

PCB depth mm	Packs of	Model No. RP	
		Snap-in fastening/screw-fastening ¹⁾	Snap-in fastening
160	1	3684.657	3684.654
220	1	3684.658	3684.655
280	1	3684.659	3684.656



Also required:

¹⁾ Assembly screws, packs of 100, Model No. RP 3654.360, see page 576.



Plastic guide rails

for contact spring fitting

For 160, 220 and 280 mm PCBs up to 2 mm nominal thickness. By installing contact springs, an electrical connection can be made between the PCB and the assembly.

Material:

Polycarbonate, base material to UL 94-V0

PCB depth mm	Packs of	Model No. RP
160	1	3684.660
220	1	3684.661
280	1	3684.662



Accessories:

Contact springs, see page 510.