

Radiant Heater and Fan Heater series FLH



Heat generated by electrical equipment operating under load will prevent the accumulation of condensation. After the equipment has been switched off however it cools down and gradually adapts to the ambient temperature, thus dropping below the dew point. This is the signal that triggers the radiant heater! These sources of heat prevent the formation of condensation by raising the internal temperature a few degrees above the ambient temperature.

In the interest of evenly distributing the heat, we recommend that the requirement of heating capacity is divided among several small heaters.



Level of protection



suitable for both 50 Hz and 60 Hz



115 V ... 230 V (FLH 010-150)

Thermal data:	Radiant Heater								Fan Heater	
	FLH 010	FLH 015	FLH 030	FLH 045	FLH 060	FLH 075	FLH100	FLH 150	FLH 250	FLH 400
Heater power ($T_{\text{U}} = +20\text{ }^{\circ}\text{C}$)	10 Watt	15 Watt	30 Watt	45 Watt	60 Watt	75 Watt	100 Watt	150 Watt	250 Watt	400 Watt
Max. surface temperature approx.	55 °C	65 °C	90 °C	105 °C	105 °C	120 °C	130 °C	150 °C	70 °C	85 °C
Airflow									50 m ³ /h (50 Hz)	61 m ³ /h (60 Hz)
Duty cycle	100 %									
Heating element	PTC (positive temperature coefficient), temperature regulating								resistance type with temperature monitor	

Electrical data:

Rated voltage ¹⁾	230 V (50 / 60 Hz)								115 V or 230 V	
Rated frequency	110 - 250 V								104 - 126 V or 207 - 258 V	
Power consumption	10 Watt	15 Watt	30 Watt	45 Watt	60 Watt	75 Watt	100 Watt	150 Watt	260 Watt	410 Watt
Starting current approx.	1,0A	1,1A	1,2A	1,8A	2,5A	4,5A	5,0A	7,5A	2,2A / 1,1A	3,6A / 1,8A

¹⁾ other voltages (24V DC, 48V DC) on request

Mechanical data:

Fitting position	any, vertical position preferred								airflow vertical, exit at top	
Construction	aluminium section, anodised (light-coloured)									
Weight	250 g	250 g	250 g	250 g	450 g	510 g	510 g	770 g	1.035 g	1.200 g
Dimensions	A	A	A	A	B	B	B	C	D	E
Protection class	I								I	
Connection	cable end or plug-in terminal								plug-in terminal	
Binding post clamping area	single filament: 2 x 0,5 - 2,5 mm ² , fine multi-filament: (soldered, wire and sleeve, pin terminal) 2 x 0,5 - 1,5 mm ²									
Mounting method	snap-in mounting for 35mm profile bar in accordance with EN 50022									


Supplementary data:

Operating temperature	- 40 °C (- 40 °F) ... + 70 °C (+ 158 °F)								- 20 °C (- 4 °F) ... + 70 °C (+ 158 °F)	
Storage temperature	- 40 °C (- 40 °F) ... + 70 °C (+ 158 °F)								- 40 °C (- 40 °F) ... + 70 °C (+ 158 °F)	
System of protection	IP 44 (cable end), IP 20 (plug-in terminal), when installed as specified								IP 20, when installed as specified	
Accessories	thermostat FLZ 510, FLZ 520, FLZ 530, hygrostat FLZ 600									
Approvals	UL approval									
Optional extra									2nd protection guard	


We reserve the right to technical alterations. Subject to correction. 075000031

Mechanical data

FLH 010 - FLH 150



FLH 250 / FLH 400



We reserve the right to technical alterations, subject to correction. U/30000031