



| PART NO.      | DIM. "A"<br>±.015(0.4) |
|---------------|------------------------|
| CRLCBSR-3-01  | 3/16 (4.8)             |
| CRLCBSR-4-01  | 1/4 (6.4)              |
| CRLCBSR-5-01  | 5/16 (8.0)             |
| CRLCBSR-6-01  | 3/8 (9.5)              |
| CRLCBSR-8-01  | 1/2 (12.7)             |
| CRLCBSR-12-01 | 3/4 (19.0)             |

NOTES:

1. MATERIAL: NYLON 6/6 (RMS-01).  
FLAME RETARDANT, NYLON (RMS-19),  
AVAILABLE BY SPECIAL ORDER ONLY.  
TO ORDER, REPLACE "-01" WITH "-19"
2. MATERIAL: NYLON 4/6, HEAT STABILIZED, (RMS-109)  
AVAILABLE BY SPECIAL ORDER ONLY.  
TO ORDER, REPLACE "-01" WITH "-109".
3. COLOR: NATURAL.  
BLACK, AVAILABLE BY SPECIAL ORDER ONLY.  
TO ORDER, ADD "-B" TO PART NO.

|     |  |             |  |  |
|-----|--|-------------|--|--|
| F   | ADDED NOTE 2 (RMS-109) BY SPECIAL ORDER                          | SM 06.06.02 | TITLE: CUPPED REVERSE LOCKING CBS, ROUND HOLE                            | DWG IN IN (MM)  FINAL  |
| E   | UPDATED NOTES AND CHANGED FILE NO.                               | SM 05.08.02 |  |  |
| D   | DIM. TO S-L IN .24 (6.0)... ADDED; TABLE REDUCED; UL NOTES ADDED | PB 07.10.95 | TOLERANCES UNLESS NOTED<br>.XX=±.010<br>.XX=±.005<br>FRAC=1/64<br>ANG=1° | FILE # CRLCBSR<br>MAT'L: SEE NOTES<br>RE: RICHCO, INC.   |
| C   | DIMS IN CHASSIS THKNS PUT TO 3 PLACES                            | PB 11.23.94 | DWN: P.B.  | APP:   |
| B   | CONVERTED TO ACAD; DIM "A" WAS .411                              | PB 07.29.94 | DT: 07-29-94   | DT:  |
| A   | COMPLETE REDRAW, .40 WAS .39, .06 WAS .07, RMS-01 WAS RMS-48     | RT 03.10.94 | DT:  | PART # SEE TABLE   |
| REV | DESCRIPTION  | ENGR DATE   | DT:  | PRINT TYPE CA  |