

Glass Filled Nylon Stopping Plugs IP66 68 & NEMA 4X 6P



PD-E-4 Series Glass Filled Nylon Dome Head Stopping Plugs provide a method of filling unused entries in increased safety equipment, maintaining the certification and integrity of the equipment.

CENELEC

Sira 00ATEX3091
II 2DG E Ex e II

CSA / A Ex

Class I, Zone 1, Ex e II
Class I Division 2 ABCD
Class II EFG, Class III

Ingress Protection: IP66 68, CSA Enclosure Type (NEMA) 4X 6P
Impact Resistance: 7Nm
Ambient Temperature: -50 to +85°C
Threadforms: Metric, NPT, NPSM, ISO Pipe (BSP), PG
Materials: Durethan BKV 30 N1 30% Glass Filled Nylon
'O' Ring Material: Nitrile
Part Number: Please refer to *Part Numbering System*

Sizes Available & Dimension References

Metric	Dim Ref	NPT	Dim Ref	PG	Dim Ref
M16	B			PG7	A
M20	C	½"	C	PG9	B
M25	C	¾"	C	PG11	C
M32	C	1"	C	PG13.5	C
M40	C	1¼"	C	PG16	C
M50	C	1½"	C	PG21	C
M63	C	2"	C	PG29	C
M75	C	2½"	C	PG36	C
				PG42	C
				PG48	C

Dimensions

	A	B	C
Head Diameter	Minimum 6.0mm larger than the major thread diameter		
Hex Socket A/F	6.0	8.0	10.0
Total Length	21.5	21.5	21.5
Thread Length	16.0	16.0	16.0

For full material specifications and options please refer to *Material Specifications*.