



PART NO.	HOLE DIAMETER ±.003 [0.08]	HEAD DIAMETER	SUGGESTED TOTAL BOARD THICKNESS	HEAD HEIGHT	LENGTH	
RBF-4-8-6-8	.157(4.00)	.32(8.0)	.08-.17(2.1-4.3)	.04(1.0)	.34(8.6)	
RBF-4-11.1-8			.08-.28(2.1-7.2)		.44(11.1)	
RBF-4-15-8		.22-.42(5.7-10.7)	.59(15.0)			
RBF-4-8-6-12		.47(12.0)	.32(8.0)	.08-.17(2.1-4.3)	.06(1.5)	.34(8.6)
RBF-4-11.1-12				.08-.28(2.1-7.2)		.44(11.1)
RBF-4-15-12		.22-.42(5.7-10.7)	.59(15.0)			
RBF-4-8-6-16	.188(4.76)	.47(12.0)	.08-.17(2.1-4.3)	.08(2.0)	.34(8.6)	
RBF-4-11.1-16					.08-.28(2.1-7.2)	.44(11.1)
RBF-4-15-16		.22-.42(5.7-10.7)	.59(15.0)			
RBF-4-8-8-8		.32(8.0)	.47(12.0)	.08-.17(2.1-4.3)	.04(1.0)	.34(8.6)
RBF-4-8-11.1-8				.08-.28(2.1-7.2)		.44(11.1)
RBF-4-8-15-8		.22-.42(5.7-10.7)	.59(15.0)			
RBF-4-8-8-12	.63(16.0)	.32(8.0)	.08-.17(2.1-4.3)	.06(1.5)	.34(8.6)	
RBF-4-11.1-12			.08-.28(2.1-7.2)		.44(11.1)	
RBF-4-15-12	.22-.42(5.7-10.7)	.59(15.0)				
RBF-4-8-6-16	*.250(6.35)	.63(16.0)	.08-.17(2.1-4.3)	.08(2.0)	.34(8.6)	
RBF-4-11.1-16					.08-.28(2.1-7.2)	.44(11.1)
RBF-4-15-16		.22-.42(5.7-10.7)	.59(15.0)			
RBF-6-4-8-6-8		.32(8.0)	.47(12.0)	.08-.17(2.1-4.3)	.04(1.0)	.34(8.6)
RBF-6-4-11.1-8				.08-.28(2.1-7.2)		.44(11.1)
RBF-6-4-15-8		.22-.42(5.7-10.7)	.59(15.0)			
RBF-6-4-8-12	.47(12.0)	.32(8.0)	.08-.17(2.1-4.3)	.06(1.5)	.34(8.6)	
RBF-6-4-11.1-12			.08-.28(2.1-7.2)		.44(11.1)	
RBF-6-4-15-12	.22-.42(5.7-10.7)	.59(15.0)				
RBF-6-4-8-16	*.281(7.14)	.63(16.0)	.08-.17(2.1-4.3)	.08(2.0)	.34(8.6)	
RBF-6-4-11.1-16					.08-.28(2.1-7.2)	.44(11.1)
RBF-6-4-15-16		.22-.42(5.7-10.7)	.59(15.0)			
RBF-7-1-11.1-8		.32(8.0)	.47(12.0)	.08-.28(2.1-7.2)	.04(1.0)	.44(11.1)
RBF-7-1-15-8				.15-.42(3.8-10.7)		.59(15.0)
RBF-7-1-19-8		.27-.56(6.9-14.2)	.75(19.0)			
RBF-7-1-11.1-12	.47(12.0)	.32(8.0)	.08-.28(2.1-7.2)	.06(1.5)	.44(11.1)	
RBF-7-1-15-12			.15-.42(3.8-10.7)		.59(15.0)	
RBF-7-1-19-12	.27-.56(6.9-14.2)	.75(19.0)				
RBF-7-1-11.1-16	.63(16.0)	.32(8.0)	.08-.28(2.1-7.2)	.08(2.0)	.44(11.1)	
RBF-7-1-15-16			.15-.42(3.8-10.7)		.59(15.0)	
RBF-7-1-19-16	.27-.56(6.9-14.2)	.75(19.0)				

* FOR USE IN METAL, LEADING EDGE OF HOLE MUST BE BROKE

NOTES:
 1. MATERIAL: NYLON 6/6 (RMS-01).
 FLAME RETARDANT NYLON (RMS-19)
 AVAILABLE BY SPECIAL ORDER.
 2. COLOR: BLACK.
 NATURAL BY SPECIAL ORDER

B	SEE ECN # 917 FOR CHANGES	SK	01/18/05
A	RELEASED FOR PRODUCTION	SM	10/19/04
REV.	DESCRIPTION	ENGR.	DATE

TITLE: BARBED PUSH FASTENER		DWG IN IN [MM]	PR
CREATED USING SOLIDWORKS	FILE #: RBF	DWN: D.J.Z.	APP: DJZ
TOLERANCES UNLESS NOTED	SHEET: 1 OF 1	DT: 06/09/2004	CHKD: SJ
RE: RICHCO INC.	SHEET SIZE: B	FINAL	
RE: RICHCO INC.	ENG@RICHCO-INC.COM	PART #	PRINT TYPE
---	(773) 539-4060	SEE TABLE	CA