## **High Frequency Mounts**

3/4" hole; 1-1/8"-18 thread; Crimp on

Model	Mount Type	Coax	Connector
MMF	Permanent microwave mount for frequencies from 800 MHz to 3.0 GHz for up to .06" thick roof surfaces.	None	Male SMA*
MHFML195C**	Permanent microwave mount for frequencies from 3.0 GHz to 5.8 GHz for up to 0.046" thick roof surfaces	17 ft. Pro-Flex™ Plus 195	Loose TNC male standard. Other connector options (NF, NM, RPC) are available.
GMHFML195C**	Magnetic base microwave mount for frequencies from 3.0 GHz	12 ft. Pro-Flex™ Plus 195	Attached TNC male standard. Contact factory for other connector options.
MLFML195C	Permanent mount for frequencies from 800 MHz to 3.0 GHz for up to 0.046" thick roof surfaces	17 ft. Pro-Flex™ Plus 195	Loose TNC male standard. Contact factory for other connector options.
MHFPFP240C**	Permanent mount for frequencies from 800 MHz to 3.0 GHz for up to 0.046" thick roof surfaces	17 ft. Pro-Flex™ Plus 240	Loose TNC male standard. Contact factory for other connector options.
GMHFPFP240C**	Magnetic mount for frequencies from 800 MHz to 3.0 GHz for up to 0.046" thick roof surfaces	12 ft. Pro-Flex <sup>™</sup> Plus 240	Loose TNC male standard. Contact factory for other connector options.
GMLFML195C	Magnetic base mount for frequencies from 800 MHz to 3.0 GHz	12 ft. Pro-Flex™ Plus 195	Attached TNC male standard. Contact factory for other connector options.

## High Frequency Mounts For Thick Roof Surfaces

5/8" hole; 1-1/8"-18 thread; Crimp on

Model	Mount Type	Coax	Connector
MTPMHF**	Permanant microwave mount for frequencies from 3.0 GHz to 5.8 GHz. For surfaces up to 1-inch thick.	None	N female* connector
MVPHF**	Vandal-proof microwave mount for frequencies from 3.0 GHz to 5.8 GHz. For surfaces up to 1/2-inch thick.	None	M to N female* con- nector

<sup>\*</sup> Cable assembly with mating connector sold separately.

For other connector options, please refer to the Mobile Antenna Mounts Configurator Part Number Guide.



MMH



MHFML195C



GMHFML195C



MLFML195C



MHFPFP240C



GMLFML195C



**MTPMHF** 



**MVPHF** 

<sup>\*\*</sup> High frequency mount to be used with (B)MEFC49005HF, (B)MEFC58005HF, MEFC2327HF and MLPV4900NGP