
0501, 0501.1 - ATTENUATORS



QC10 Shown



GENERAL DESCRIPTION

The Quam QC10 (xx) is a single gang, continuous rotary, ten-step audio level attenuator with an OFF position. Except where noted, all variants are UL Listed 813.

Finish: QC10 - Stainless steel, embossed position QC10 Classic - Stainless steel, debossed, paint

filled legends

QC10P - Stainless steel, embossed position (No position on scale) (No UL Listing)
QC10RM - 2" x 2" dial scale, white on black

QC10W - Hybrid white epoxy plate, white knob

Knob (all variants, except QC10W): Black with white indicator

Knob (QC10W): White, molded indicator

INTENDED USE

QC10, QC10 Classic, QC10RM: Attenuates audio power to any number of loudspeakers up to 20W load. For use with 25V or 70.7V distributed audio systems; indoor environment.

QC10P: (No UL Listing) Attenuates audio level output to any number of loudspeakers up to 20W load. For use with 25V or 70.7V distributed audio systems; indoor environment. When internal 24VDC relay is activated, attenuator function is bypassed.

Program Material: Signal tones, voice and music

SYSTEM COMPONENTS

N/A

RECOMMENDED ADDITIONAL QUAM COMPONENTS

0403 - Surface Mounting Devices SE4W Single Gang Box

AUDIO SPECIFICATIONS

Power Rating	20W continuous
Attenuation	Position 10, Full signal
(Ref: 25V,70.7V line)	Positions 9-3, -3 dB each
	Positions 2-1, -6 dB each
	Position 0, -36 dB
Insertion Loss	< 0.5 dB

MECHANICAL SPECIFICATIONS

Recommended construction sequences, installation instructions and A&E Specifications are available in various formats on the Quam Architects' and Engineers' Resources CD or on the web at: www.quamspeakers.com

Quam-Nichols Company

234 East Marquette Road, Chicago, IL 60637 Phone: (800) NEED NOW Fax: (888) NEED NOW (800) 633 - 3669 (888) 633 - 3669

E-Mail: neednow@gnc.com www.quamspeakers.com

© 2011 Quam-Nichols Company Quam-Nichols reserves the right to make changes and/or improvements to its products at any time and without notice.