SLx Gold Signal Amplifiers





The SLx range of Gold Signal aerial ampli-The SEX range of Gold Signal aerial amplifiers are designed to improve picture and sound quality by amplifying weak UHF, VHF, DAB and FM radio signals. Can also be used to distribute VCR, Digital TV and Sky/Sky+signals without loss of reception.

- Unlike standard boosters SLx Gold's flat gain response across full frequency spectrum ensures optimum digital reception
- ception

 Dedicated inputs for UHF and FM/DAB
 Side mounted terminals provide easy cable management
 Infra-red by-pass for digilinks
 Surge Protection
 Full VHF compatability for TV and FM/DAB including training

- DAB including Ireland
- Integrated by-pass to control Digital satellite receivers from a second TV

Inputs Outputs Frequency Range (UHF MHz) Frequency Range (VHF MHz) Gain Noise Figure Isolation Loss Weight Dimensions (WxDxH)mm	\$Lx2 2 2 470-862 47-300 12dB <4dB 22dB 440g 172x75x46	SLx4 2 4 470-862 47-300 8dB <4dB 22dB 517g 207x75x46	SLx6 2 6 470-862 47-300 8dB <4dB 22dB 740g 285x85x50	SLx8 2 8 470-862 47-300 8dB <4dB 22dB 750g 285x85x50 447536.428071

		Price Each
Model	Order Code	
SLx2	127-1331	
SLx4	127-1332	
SLx6	127-1333	
SLx8	127-1334	
SLx4 F Type	127-1336	
SLx6 F Type	127-1338	
SLx8 F Type	127-1339	