


	PART NO.		REVISIONS									
			REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE		
	HK-GDP04	-	Α	RELEASED	Arun	07/02/11	Jagan	07/02/11	Farnell	21/02/11		



Dimensions : Millimetres

Packing: (6)

Specifications:

Cable Wiring

32AWG (7/0.08mmTA) x 1P + D (7/0.08mmTA) + AM x 5C + 32AWG (7/0.08mmTA) x 5C + AD (7/0.08mmTA) + B (16 x 7/0.12mmTA) (Coverage 85%).

Jacket material : PVC OD: 5 ±0.1m.

Cable length : 0.15m.
Cable colour : White.

Connector A

Mini DisplayPort 20P male solder type (with PCB) Insulation : Black.

Contact : Phosphor bronze, gold plated.

Shell : Fe, nickel plated.

Connector B

HDMI 19P female solder type

Insulation : Black.

Contact : Phosphor bronze, gold plated.

Shell : Fe, gold plated.

Over mould : Assembly, white.

Parameter Settings

 $\begin{array}{ll} \mbox{Conductive resistance} & : 1.0 \Omega. \\ \mbox{Minimum insulative resistance} & : 10 M \Omega. \end{array}$

Hi-Pot : DC 300V/10ms, 1.5mA/I, 50Hz, 0.03s.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

DP to HDMI Adaptor

Part Number Table

Description

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

Part Number

HK-GDP04

DRAWN BY:	DATE:	DRAWING TITLE			
Arun	07/02/11				
CHECKED BY:	DATE:	SIZE	DWG N		
Jagan	07/02/11	Α			
APPROVED BY:	DATE:	- 			
Farnell	21/02/11	SCAL	E: NTS		

	DRAW	DRAWING TITLE.							
	DP to HDMI Adaptor - 150mm								
	SIZE A	DWG NO.	XXX	ELECTRONIC FILE HK-GDP04_DWG				REV A	
_	SCAL	E: NTS	U.O.M.: mm		SHEET:	1	OF	1	