



WIDE DISPERSION SPEAKER

Dims198mm dia x 250mm

An omni-directional suspension speaker with a water-resistant cone and a plastic casing, making it suitable for indoor or outdoor use. Input is selectable for 100V line or low impedance use via a rotary switch and a 'U' bracket is supplied for mounting.

Driver	ne
Power rating RMS15	W
Power	ns
SPL	зB



OUTDOOR SPEAKER

Weatherproof outdoor. Suitable for music and speech. Adjustable metal fixing bracket. Rugged 6.5in. heavy duty speaker unit with weatherproof cone. Fitted 100V line matching transformer with 15W/8W/4W/2W/Off and direct tapping, for 8Ω selectable by rotary switch. For use in patio, by swimming pool, garden, etc.

Power rating RMS .	
Speaker:	6.5in. (weatherproof)
u	

Frequency response	e150-10000Hz
Sensitivity	
Dims	
Weight	1.84kg

HMS10 MARINE/ALL WEATHER SPEAKER For water craft, vehicles or general

outdoor use, 10 watt/8 ohms horn driver sealed to operate under most adverse conditions. Adjustable bracket with 3 fixing holes set

Power rating10W RMS Impedance 8Ω Frequency response400Hz - 15kHz

Dims150mm dia. x 140mm

Sensitivity100dB Weight1.2kg

P630F

38mm apart.

200
200
200
이 가지 않는 것이 같은 것이 같은 것이 말했다. 👔
2




HEAVY-DUTY SPEAKER

An 8W speaker for 100V line applications in a tough, sheet steel case to give remarkable protection against impact or vandalism. For extra security, the double steel grille can only be removed using the Allen keys supplied. Finished in grey enamel, it has a 20mm conduit cable entry.

Power rating	
Taps	
Sensitivity	
Max. SPL	99dB(A) @ 1m
Frequency response	140-11000Hz





WATERPROOF 'BULKHEAD' LOUDSPEAKER

Well made quality loudspeaker of attractive appearance. Ideal for use in bathrooms, kitchens or conservatories. Wide frequency range offers hi-fi quality up to 20W max. Can readily be adapted for 100V line use with the addition of Altai line matching transformer. The unit is supplied with a metal backplate for wall fixing or mounting directly on to a simple 13A socket backbox. The high flux full range speaker unit is fitted with an ABS plastic case.

Power rating RMS	10W	Dims	230 x 158 x 86mm
Frequency response		Weight	1kg
Frequency response Downloaded from Elcodis.com Sensitivity (Im IW	electronic comp	onents distributor	lvorv

MARINE SPEAKERS

High quality co-axial speaker systems for use in marine environments. The baskets and grilles are moulded in UV protected plastic, with moulded-in magnet assemblies. Both woofers and tweeters have polypropylene cones and the woofers have treated fabric surrounds. Supplied with fixing kits.

130mm (5in.)
Max power
RMS power
Frequency response80Hz - 20kHz
Speaker sizes125mm woofer
Impedance4Ω
Mounting depth
Overall diameter154mm
Cut-out diameter
Weight1.18kg

B302

B30'

165mm (6 5in)

rosinn (ö.sin.)
Max power
RMS power
Frequency response60Hz - 20kHz
Speaker sizes165mm woofer,
Impedance4Ω
Mounting depth
Overall diameter





