

EPITOME® SPEAKER BRACKETS



Fig. 1



Fig. 2



Fig. 3

Speakers Mounts

Retail Part No.	Figure Number	Description	Quantity
30-3400	1	Speaker Mounts-Black	1 Pair
30-3401	1	Speaker Mount-White	1 Pair
30-4005	2	5 1/4" Ceiling Bracket	1 Pair
30-4006	2	6 1/2" Ceiling Bracket	1 Pair
30-4015	3	5 1/4" In-Wall Rough-In Bracket	1 Pair
30-4016	3	6 1/2" In-Wall Rough-In Bracket	1 Pair
30-4018	3	8" In-Wall Rough-In Bracket	1 Pair

DISTRIBUTION PRODUCTS



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10

Distribution Products

Retail Part No.	Figure Number	Description	Watts (RMS)/(MAX)	Features
65-2005	4	6 Pair In-Wall Speaker Selector	100/200	2 Source; Selectable Impedance Protection
65-2025	5	Stereo Distribution Box	300(OFF);180(ON)	8 Stereo Inputs; 10/20 AWG Wire
30-1515	6	Home Theatre Wall Panel	N/A	Right, Left, Front & Rear & Center Spring Clips; 2 Woofer Plugs
30-382	7	Custom Speaker Wall Plate	N/A	Binding Posts Accepts Bare Wire, Pin Plugs, Spade Lugs or Banana plugs
65-2020	8	2 Source A/B Speaker Selector	N/A	Chose A or B Speakers or Both; 18 AWG Wire
65-7012	9	50 Watt 4 Pair Speaker Selector	50/25	Four Pairs Operate From One Source; Up to 14 AWG Wire
65-8712	10	200 Watt 6 Pair Speaker Selector	200/100	Six Pairs Operate From One Source; Up to 14 AWG Wire

VOLUME CONTROLS



Fig. 11



Fig. 12



Fig. 13



Fig. 14



Fig. 15

Volume Controls

Retail Part No.	Figure Number	Description	Color	Specifications
30-315	11	Cabinet Mounting Type	Black	10 watts peak audio. For use with 8-16 ohm speakers. Single "L" pad
30-316	11	Cabinet Mounting Type	Black	10 watts peak audio. For use with 8-16 ohm speakers. Stereo "LL" pad
30-364	12	Wall Mounting Type	Black	10 watts peak audio. For use with 8-16 ohm speakers. Single "L" pad
30-372	12	Wall Mounting Type	Black	10 watts peak audio. For use with 8-16 ohm speakers. Stereo "LL" pad
65-1530	13	10 Step Stereo Volume Control-Standard	White	25 watts rms, 75 watts (avg), 8 ohms, 35Hz-20kHz, 30dB(max).10 switch steps
65-1620	14	10 Step Stereo Volume Control-Décor	White	25 watts rms, 75 watts (avg), 8 ohms, 35Hz-20kHz, 30dB(max).10 switch steps
65-3610*	15	12 Step Adj. Impedance Vol. Control-Standard	White	216 watts (max), 2-32 ohms, 35Hz-20kHz, 34dB in 12 steps, 3dB in 8
65-3611*	15	12 Step Adj. Impedance Vol. Control-Standard	Ivory	216 watts (max), 2-32 ohms, 35Hz-20kHz, 34dB in 12 steps, 3dB in 8
65-3635*	15	12 Step Adj. Impedance Vol. Control-Décor	White	216 watts (max), 2-32 ohms, 35Hz-20kHz, 34dB in 12 steps, 3dB in 8
65-3636*	15	12 Step Adj. Impedance Vol. Control-Décor	Ivory	216 watts (max), 2-32 ohms, 35Hz-20kHz, 34dB in 12 steps, 3dB in 8

*Requires 4" deep box