152-662 666-361 891-629/630

Cretchiey Label Technology Limited

Links Whaters Close Pen fo and it remail Estate State - Tweet Hell 185 United Kingdom

Tu -44 (0) 1493 244600 Ftr +44 (0, 1495 241736



COMPUTER PRINTABLE DESTRUCTIBLE VINYL

PRODUCT 03-132

Face Stock 2 mil Matte

Printability CITC4 Topcoat

Adhesive/Thickness PA-T1 Adhesive 0.8 mil (20 micron)

Release Liner 8 (K)

White Destructible Vinyl

Printability: CITC4 is a matte white topcoating designed for computer, typewriter, thermal

transfer, impact and other mechanical printing processes.

PA-T1 is a strong, permanent solvent acrylic adhesive with proven performance for Adhesive:

standard labels, nameplates and other similar products. It has high cohesion and good resistance to heat, cold water and UV. It also has good tack, peel and shear strength with excellent adhesion to low energy surfaces. It is designed for high speed

automatic label application.

Liner: The 8 (K) liner is a 50 pound, 2.8 mil glassine paper with silicone coating. This liner is specifically designed to facilitate rotary die cutting and is primarily used in roll

label applications.

GENERAL CHARACTERISTICS

Adhesion:

Not measurable due to the destructible characteristics of the vinyl.

Tensile Strength:

MD and CD = 1.5 to 2.5 kg/mm

Flexibility:

Successfully applied to stainless steel, glass and painted steel. Minimal

to no edge lift after 24 hours.

Dimensional Stability:

Good

Chemical Resistance:

Applied labels generally found to be resistant to water, mild acids, salt and alkalis, petroleum based greases, oils and aliphatic solvents.

Minimum Application

Temperature:

 $+40^{\circ}F(+4^{\circ}C)$

Service Temperature

Range:

-50°F (-46°C) to +200°F (+93°C)

Outdoor Durability:

One year when properly processed and placed under normal vertical exposure conditions.