

TECHNICAL DATASHEET

Doc. No:
TTDS 193 Rev1

Tyco Electronics LEB-...P-8A

LEB-...P-8A self-adhesive laser printer labels.

Label material	Polyester film, matt silver		
Adhesive	Permanent pressure sensitive acrylic		
Thickness:			
Label	0.05 mm ±10%	ASTM D374-88	
Peel Adhesion	Stainless steel	1400 N/m	FTM 1 (72 hour dwell) Average values
Service Temperature	-40°C to +120 °C		
Minimum application temperature	10 °C		
Print permanence	Dry rub		SAE-AS-81531
Laser jet - 6 sheets/min	Print legible after 320 rubs		
Storage stability	2 years at 21°C and 50% RH without direct sunlight		
Printability	Laserprinter		

Tyco Electronics idento GmbH
Paul-Ehrlich-Straße 23
D-63322 Rödermark
Tel.: 06074/8908-0

Tyco Electronics Identto
ZI de Comboire - 1 rue des
Montagnes de Lans
F-38130 Echirolles
Phone: +33 (0) 476 099 696

Author: M Priddle
Print date: 29-Jun-10
Updated:
Page: 1 of 1

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics Corporation makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics' only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.