Our most popular beacon is now even better!





Features

- NEW! belt drive mechanism
- All models 12/24V*
- 4 popular mounting options
- Low profile lens
- Advanced reflector technology gives up to 20% increase in light output
- Extended 2 Year Warranty
- Available in amber, blue, red and green

* Requires belt adjustment

See over for part number guide and technical specifications





TECHNICAL SPECIFICATIONS

1 Bolt

- LBB122 amber
- LBB122C blue
- LBB122R red
- LBB122G green

3 Bolt

- LBB255K amber
- LBB255C
- LBB255R red
- LBB255G green


Magnetic

- LBB260K amber
- LBB260C blue
- LBB260R
- LBB260G green


Flexi DIN

- LBB272 amber
- LBB272C blue
- LBB272R red
- LBB272G green



















Specification

Voltage: 12/24V

Flash rate: 160 FPM

Temperature

range: -20°C to +50°C

Lens

material: Polycarbonate

Amps: 4.6A @ 12V

3.0A @ 24V

Bulb: H1 12V 55W

included

Approvals

ECE Reg 65 'E' (amber only)

ECE Reg 10 'E'



Lucas Warning & Safety Victoria Industrial Estate Victoria Road Leeds LS14 2LA

Tel: 0870 608 0763 Fax: 0113 237 5630