

solex



	Solex 3	Solex 10	Solex 15
	9 ~ 60Vdc		
	85 mA (@12V) 40 mA (@24V) 25 mA (@48V)	185 mA (@12V) 88 mA (@24V) 45 mA (@48V)	510 mA (@12V) 240 mA (@24V) 120 mA (@48V)
	Current values @ 12,24, and 48V are +/- 10%		
	0.28mm ² ~ 2.5mm ²		
	-25°C ~ +70°C		
	ABS V0 & PC		
	S = Type A = IP21C (IP54*) D/U = Type B = IP33C (IP65*)		
	1Hz		

*Product exceeds minimum requirements of EN54-3
See www.fulleon.com
Le produit dépasse les exigences minimum de EN54-3
Voir www.fulleon.com
Das Erzeugnis erfüllt die Mindestanforderungen von EN54-3.
Siehe www.fulleon.com
Il prodotto supera i requisiti minimi previsti dalla norma EN54-3
Vedi www.fulleon.com
Product overtreft de minimale vereisten van EN54-3.
Zie www.fulleon.com
El producto excede los requisitos mínimos de la norma EN54-3
Véase www.fulleon.com
Produkten överträffar minsta krav enligt EN54-3
Se www.fulleon.com



www.fulleon.com
Fulleon Ltd, Cwmbrian, South Wales, U.K. G207018
25-6018 Iss C

