

Pt 100 Probes

| | General purpose | | Immersion | | Insertion | | Air probe | |
|-----------------------------------------------------------|------------------------|------------------------|-------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Probe type | SE011 | SE019 | SE012 | SE014 | SE015 | SE016 | SE017 | SE018 |
| Temperature range | -30 to +200 °C | -75 to +260 °C | -50 to +250 °C | -75 to +250 °C | -75 to +250 °C | -150 to +650 °C | -75 to +250 °C | -150 to +650 °C |
| Accuracy | ±0.15 °C @ 0 °C | ±0.15 °C @ 0 °C | ±0.03 °C @ 0 °C | ±0.15 °C @ 0 °C | ±0.15 °C @ 0 °C | ±0.15 °C @ 0 °C | ±0.15 °C @ 0 °C | ±0.15 °C @ 0 °C |
| Dimensions: Length (mm) Diameter (mm): Cable (m) | 150 6 2 | 120 3 2 | 150 4 2 | 120 3.3 2 | 120 3.3 2 | 150 4 2 | 120 3.3 2 | 150 4 2 |
| Material | s/s probe PVC cable | s/s probe PVC cable | s/s probe PTFE cable | s/s probe PVC cable | s/s probe PVC cable | s/s probe PVC cable | s/s probe PVC cable | s/s probe PVC cable |
| Handle | No | Yes | No | Yes | Yes | Yes | Yes | Yes |
| Order code | | 1671127 | | 1671123 | | 1671124 | 1671125 | 1671126 |