Dec-Ranger[™] **Decade Resistance Selector**



A precision, ±0.1% accuracy, decade resistance box. The unit has a sturdy metal housing, universal binding posts and a grounded metal post for effective shielding.

FEATURES

- · Rotary tap switches operate in either direction.
- · Direct digital readout.


SPECIFICATIONS

Power: 1/4 watt per resistor. Accuracy: ±0.1% (plus 0.03 ohms maximum contact and circuit resistance) TC of resistors: ±20 PPM/°C Number of decades: 6 Range: 1 ohm thru 1,111,110 ohms in 1 ohm increments Switch life: in excess of 50,000 operations Dimensions: 10¹/2" wide, 3³/4" high, 45/8" deep

Weight: 3 lbs. 10 oz.

Ohm-Ranger[®]

Resistance Selector



An economical, portable resistance selector with a range to over 11,000,000 ohms, in 1 ohm increments. Has three binding posts, one to ground the case.

FEATURES

- · Sliding switches.
- Handy slimline size.
- Rugged metal construction.

S P E C I F I C A T I O N S

Power: 0.5 watts (Do not exceed 250V).

- Accuracy: ±1.0% (10 ohms and over).
- ±5.0% (9.99 ohms and under). Number of decades: 7

Range: 1 ohm thru 11,111,110 ohms in 1 ohm increments.

Weight: 13 oz.

Cap-Ranger[®]

Capacitance Selector



An economical, portable capacitance selector with three binding posts, one to ground the metal case.

FEATURES

- · Sliding switches
- · Handy compact size
- Rugged metal construction

S P E C I F I C A T I O N S

Accuracy: ±2%.

Maximum voltage: 200 VDC. Residual capacitance: 60 pf (typical).

Range: 100 picofarads to 11.111 microfarads in 100 picofarad steps.

Dimensions: 4" x 6" x 1". Weight: 13 oz.