



REVISIONS

DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1190	A	RELEASED	JWM	10/25/02	HO	10/25/02	DJC	10/25/02



FEATURES:

- 0.2Hz to 20MHz frequency Range
- 10mV to 20V pk-pk from 50Ω
- TTL/CMOS auxilliary output
- DC offset control with zero detent
- Variable symmetry control
- External sweep input

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	10/25/02	20MHz Function Generator			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Hisham Odish	10/25/02	A	72-6859	19C7731.dwg	A
APPROVED BY:	DATE:	SCALE:	U.O.M.:	SHEET:		
John Cole	10/25/02	NTS	Millimeters [Inches]	1 OF 2		

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

Technical Specifications

FREQUENCY

Frequency Range: 0.2Hz to 20MHz in 8 overlapping decade ranges with fine adjustment by a vernier.

Vernier Range: >10:1 on each range.

Vernier Accuracy: Typically $\pm 5\%$ of full scale.

SWEEP MODE (EXTERNAL)

Input Impedance: 82 k Ω

Sweep Range: Typically > 20:1

Input Sensitivity: Typically 0 to 2V for 10:1 sweep

Max. Input Voltage: $\pm 10V$

Max. Slew Rate of sweep voltage: 0.1V/us

OPERATING MODES

(Specifications apply for the top decade of each frequency range and output 10V peak-to-peak into 50 Ω termination).

SINE

Distortion: Typically 2% on 200, 2k and 20k ranges.

Amplitude Flatness: $\pm 0.2dB$ to 200kHz; $\pm 2dB$ to 20MHz.

TRIANGLE

Linearity: Typically 99% on kHz ranges.

SQUAREWAVE

Rise and Fall Times: <22ns

DC

Range: $\pm 10V$ from 50 Ω

SYMMETRY

Symmetry Range: Typically variable from 1:6 to 6:1 up to 500kHz.

OUTPUTS

50 Ω

Three switch-selectable ranges with 26dB vernier control within each range.

0dB Range: 1V to 20V peak-to-peak (0.5V to 10V into 50 Ω).

-20dB Range: 100mV to 2V peak-to-peak (50mV to 1V into 50 Ω)

-40dB Range: 10mV to 0.2V peak-to-peak (5mV to 0.1V into 50 Ω)

DC Offset Range: $\pm 10V$ from 50 Ω . DC offset plus signal peak limited to $\pm 10V$ ($\pm 5V$ into 50 Ω). DC offset plus waveform attenuated proportionally in -20dB and -40dB position.

TTL/CMOS

Capable of driving 4 standard TTL loads.

GENERAL

Power: 115V nominal 50/60Hz operating range $\pm 14\%$ of nominal; 30VA max. Installation Category II.

Operating Range: +5 $^{\circ}C$ to +40 $^{\circ}C$, 20% to 80% RH.

Storage Range: -10 $^{\circ}C$ to +65 $^{\circ}C$

Environmental: Indoor use at altitudes to 2000m, Pollution Degree 1.

Electrical Safety: Complies with EN61010-1.

EMC: Complies with EN55011 and EN50082-1.

Size: 220(W) x 82(H) x 230(D) mm, (10.3 x 3.4 x 9.2") excluding feet.

Weight: 1.5 Kg (3.3lb).