



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1308

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1994	A	RELEASED	JN	08/26/08	JWM	08/28/08	JWM	08/26/08



SPC P/N	Max. Measuring Range			Precision	Response Frequency	Power Supply	Charging Time	Service Duration after Fully Charged	Volume	Battery Life Span	Weight
	Kgf.cm	N.m	Lbf.in								
SLDHP10	0.15-10	0.015-1.0	0.15-9.0	±1	600Hz	5pcs. Of 1.2V Ni-cd batteries	8hrs (special charger used)	30hrs	123x230x65mm	More than 300times	1.8kg
SLDHP50	1.5-50	0.15-5.0	0.15-44.0								
SLDHP100	1.5-100	0.15-10.0	0.15-90.0								

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Jason Nash	08/26/08
CHECKED BY:	DATE:
JWM	08/26/08
APPROVED BY:	DATE:
JWM	08/26/08

DRAWING TITLE: Digital Torque Meter			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	Ta-929	Ta-929.dwg	A
SCALE: NTS		U.Q.M.: INCHES [mm]	SHEET: 1 OF 1