

Farnell Order Code: 1641054

FOX MODEL: FXO-HC536R-80 FOX Part Number: 767-80-20

HCMOS, CERAMIC, SMD, OSCILLATOR

Specifications

80.000 MHz ±25 PPM		
±25 PPM		
40000500		
4000 .0500		
-40°C ~ +85°C		
-55°C ~ +125°C		
3.3V ± 5%		
47 mA Max		
10% V _{DD} Max		
90% V _{DD} Min		
45% ~ 55%		
3 nS Max		
3 nS Max		
15 pF Max		
10 ms Max		
100 nS Max		
< 1.1pS Typ.		
260°C / 10 Seconds		
1		
Au		

¹ Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock, and vibration.

²An internal pullup resistor from pin 1 to pin 4 allows active output if pin 1 is left open.

ENABLE/DISABLE FUNCTION ²				
Pin 1	1 OUTPUT (Pin 3)			
OPEN ²	ACTIVE			
'1' Level VIH ≥ 70%V _{DD}	ACTIVE			
'0' Level VIL ≤ 30%V _{DD}	High Z			

NOTE: A $0.01\mu F$ bypass capacitor should be placed between V_{DD} (Pin4) and GND (Pin 2) to minimize power supply line noise.


RoHS Compliance Status: Compliant




Drawing is for reference to critical specifications defined by size measurements.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary

Mechanical / Dimensions (millimeters):






Note: XPRESSO HCMOS XOs are designed to fit on industry standard, 4 pad, layouts.

Pin Connections
#1) E/D #3 Output
#2 GND #4 VDD
*TP are test points and are NC

Recommended Circuit



NOTE: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies

Reference / Comments	Title / Description: Product Specifications			
	Drawing Number: DWG-4548-36 Rev: 1			Size: A
	Part Number: 767-80-20			Cage: 61429
	Draftsperson: AR Approved: BN		Date: 08/25/2008	