

Farnell Order Code: 1641010

FOX MODEL: FXO-HC736R-33.333333 FOX Part Number: 768-33.333333-4

HCMOS, CERAMIC, SMD, OSCILLATOR

A. Specifications

33.333333 MHz		
±25 PPM		
-40°C ~ +85°C		
-55°C ~ +125°C		
3.3V ± 5%		
35 mA Max		
10% V _{DD} Max		
90% V _{DD} Min		
45% ~ 55%		
3 nS Max		
3 nS Max		
15 pF Max		
10 ms Max		
100 nS Max		
< 1.1 pS Typ.		
260°C / 10 Seconds		
1		
Au		

 $^{^{\}rm 1}$ Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock, and vibration.

²An internal pullup resistor from pin 1 to pin 4 allows active output if pin 1 is left open.

ENABLE/DISABLE FUNCTION ²				
Pin 1	OUTPUT (Pin 3)			
OPEN ²	ACTIVE			
'1' Level VIH ≥ 70%V _{DD}	ACTIVE			
'0' Level VIL ≤ 30%V _{DD}	High Z			

NOTE: A $0.01\mu F$ bypass capacitor should be placed between V_{DD} (Pin4) and GND (Pin 2) to minimize power supply line noise.


RoHS Compliance Status: Compliant




Drawing is for reference to critical specifications defined by size measurements.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary


B. Mechanical / Dimensions (millimeters):





Note: XPRESSO HCMOS XOs are designed to fit or industry standard, 4 pad, layouts.

Pin Connections #1) E/D #3 Output #2 GND #4 VDD *TP are test points and are NC



<u>NOTE</u>: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

Reference / Comments	Title / Description: Product Specifications			
	Drawing Number: DWG-4549-28 Rev: 1 Part Number: 768-33.333333-4			Size: A
				Cage: 61429
	Draftsperson: AR Approved: BN		N	Date: 08/25/2008