

Farnell Order Code: 1641020

FOX MODEL: FXO-HC536R-1 FOX Part Number: 767-1-7

HCMOS, CERAMIC, SMD, OSCILLATOR

Specifications

Specifications			
Parameters			
Frequency	1.000 MHz		
Frequency Stability 1	±25 PPM		
Temperature Range			
Operating (T _{OPR})	-40°C ~ +85°C		
Storage (T _{STG})	-55°C ~ +125°C		
Supply Voltage (V _{DD})	3.3V ± 5%		
Input Current (I _{DD})	32 mA Max		
Output Voltage (V _{OL})	10% V _{DD} Max		
(V _{OH})	90% V _{DD} Min		
Output Symmetry (50% V _{p-p} Level)	45% ~ 55%		
Rise Time (10% ~ 90% V _{p-p}) (TR)	3 nS Max		
Fall Time (90% ~ 10% V _{p-p}) (TF)	3 nS Max		
Output Load (HCMOS)	15 pF Max		
Startup Time (T _S)	10 ms Max		
Output Enable / Disable Time ²	100 nS Max		
Phase Jitter (12kHz ~ 20MHz)	< 1.1pS Typ.		
Maximum Soldering Temp / Time	260°C / 10 Seconds		
Moisture Sensitivity Level (MSL)	1		
Termination Finish	Au		

¹ Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock, and vibration.

²An internal pullup resistor from pin 1 to pin 4 allows active output if pin 1 is left open.

ENABLE/DISABLE FUNCTION ²				
Pin 1 OUTPUT (Pin 3)				
OPEN ²	ACTIVE			
'1' Level VIH ≥ 70%V _{DD}	ACTIVE			
'0' Level VIL ≤ 30%V _{DD}	High Z			

NOTE: A $0.01\mu F$ bypass capacitor should be placed between V_{DD} (Pin4) and GND (Pin 2) to minimize power supply line noise.


RoHS Compliance Status: Compliant




Drawing is for reference to critical specifications defined by size measurements.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary

Mechanical / Dimensions (millimeters):






Note: XPRESSO HCMOS XOs are designed to fit on industry standard, 4 pad, layouts.

Pin Connections
#1) E/D #3 Output
#2 GND #4 VDD
*TP are test points and are NC

Recommended Circuit



<u>NOTE</u>: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

Drawing Number: DWG-4548-6 Rev: 1 Size: A Part Number: 767-1-7 Cage: 61429 Profferorson: AB Approved: BN Date: 09/05/2009	Reference / Comments	Title / Description: Product Specifications					
					Size: A		
Draftsparson: AP Approved: RN Date: 09/25/2009					Cage: 61429		
Dialisperson. An Approved. Bit Date. 00/23/2000		Draftsperson: AR Approved: BN		N	Date: 08/25/2008		