

# AC 5E



## SIZE :

170x150x55mm (6.69"x5.91"x2.17")

## CONSTRUCTION :

- Die-cast aluminum housing
- Metal impeller or Glass fiber reinforced plastic: Impeller are UL 94V-0 rating
- Shaded pole motor
- Impedance protected
- Leader wire available

## OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

## WEIGHT :

1000 grams



## Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED	FREQUENCY	MAX. RATED	MAX. INPUT	SPEED	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE
		VOLTAGE					CURRENT	POWER	R.P.M.	m <sup>3</sup> /min	
5E-200B	Ball	200	50/60	300/260	46/44	2600/2700	4.92/5.21	174/184	10.17/10.23	0.40/0.41	50/53
5E-115B	Ball	115	50/60	640/540	48/46	2750/3100	5.66/6.79	200/240	12.30/13.70	0.48/0.54	50/53
5E-230B	Ball	230	50/60	300/260	46/44	2750/3100	5.66/6.79	200/240	12.30/13.70	0.48/0.54	50/53
5E-DVB	Ball	230/115	50/60	310/600	47/47	2750/3100	5.66/6.79	200/240	12.30/13.70	0.48/0.54	50/53
5P-115B	Ball	115	50/60	640/540	48/42	2850/3400	5.38/6.51	190/230	12.30/13.70	0.48/0.54	50/53
5P-230B	Ball	230	50/60	280/240	46/40	2850/3400	5.38/6.51	190/230	12.30/13.70	0.48/0.54	50/53
5E-DVB-1	Ball	200/100	50/60	330/620	45/50	2750/3100	5.66/6.79	200/240	12.30/13.70	0.48/0.54	50/53

## Dimensions (mm)

## Performance Curve

