



6200N Series

Tubeaxial

Ø 172x51mm

- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics. With electronic protection against reverse polarity and blocking; electronic motor current limitation in the start-up phase when rotor is blocked.
- Metal fan housing, impeller of fiber-glass reinforced plastic PA.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Electrical connection via 2 flat pins 3 x 0.5 mm. Housing with ground lug for screw M4 x 8 (TORX).
- UL, CSA, VDE approvals on some models, please contact application engineering.
- Mounting from either face using two 4.3 mm holes.

Part Number	CFM @ 0	Curve	Volts	Voltage Range	Power (W)	dBA	Max Ambient Temp C	Wgt. (lbs)	Type Of Bearing	Features
6212NM	206	1	12	8 to 15	12.0	50	72	1.75	Ball	Terminals
6224NM	206	1	24	12 to 32	12.0	50	72	1.75	Ball	Terminals
6224N	241	2	24	12 to 28	18.0	55	72	1.75	Ball	Terminals
6224N/2	241	2	24	12 to 28	18.0	55	72	1.75	Ball	Terminals
6224N/12	241	2	24	12 to 28	18.0	55	72	1.75	Ball	Terminals
6224NH	283	3	24	12 to 28	26.0	61	72	1.75	Ball	Terminals
6248NM	206	1	48	28 to 60	12.0	50	72	1.75	Ball	Terminals
6248N	241	2	48	28 to 60	17.0	55	72	1.75	Ball	Terminals
6248N/2	241	2	48	28 to 60	17.0	55	72	1.75	Ball	Terminals
6248N/12	241	2	48	28 to 60	17.0	55	72	1.75	Ball	Terminals

