BW Series












Dim. A			Rρ
Model	mm (inches)	Hole	R _e (°C/W)
BW38-2	38.00 (1.496)	No	7.3
BW38-4	38.00 (1.496)	Yes	7.3
BW50-2	50.00 (1.969)	No	5.9

Dim. A			RA	
Model	mm (inches)	Hole	R _e (°C/W)	
BW50-4	50.00 (1.969)	Yes	5.9	
BW63-2	63.00 (2.480)	No	4.7	
BW63-4	63.00 (2.480)	Yes	4.7	



AIR VELOCITY

m/sec 0 1.0 2.0 3.0 4.0 5.0

ft/min 0 200 400 600 800 1000

ft/min 0 200 400 600 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000

10 0 800 1000


10 0 800 1000

10 0 800 1000


10 0 800 1000

10 0 800 1000

10 0 8



Recommended PCB Hole Layout:





▲ BW63-4

Alternative:

 ${\it Use spring clip~6801 with~-2 variants.}$

ML32







 $\begin{array}{ll} \text{Model} & \textbf{R}_{\theta} \, (^{\circ} \textbf{C/W}) \\ \text{ML32} \, ---- 9.0 \end{array}$



