

## Attachable heatsink

A

B

C

D

E

F

G

H





I

K















L

M

N

|   |   |   |
|---|---|---|
|  |  |  |
| <b>art. no.</b>   |  | $R_{th}$ [K/W]  |
| <b>FK 220 SA 220</b>  | TO 220  | 25  |

surface: black anodised

|   |   |   |   |                         |  |   |
|---|---|---|---|-------------------------|--|---|
|    |  |  |   |                         |  |   |
| <b>art. no.</b>   |  | $R_{th}$ [K/W]  |   |                         |  |   |
| <b>FK 224 ... P SIP</b>   | P SIP   | 18  |   |                         |  |   |
|  | <b>FK 224 ... 218 1</b>   |   |   | <b>FK 224 ... 218 2</b> |   |   |
|   | <b>FK 224 ... 220 1</b>   |  |  | <b>FK 224 ... 220 2</b> |  |  |
|   | <b>art. no.</b>   |  | $R_{th}$ [K/W]  |                         |  |   |
|   | <b>FK 224 ... 218 1</b>   | TO 218  | 18  |                         |  |   |
|   | <b>FK 224 ... 218 2</b>   | TO 218  | 18  |                         |  |   |
| <b>FK 224 ... 220 1</b>   | TO 220  | 18  |   |                         |  |   |
| <b>FK 224 ... 220 2</b>   | TO 220  | 18  |   |                         |  |   |
| <b>please indicate:</b>   | ... surface treatment<br>SA=black anodised<br>MI=solderable                       |   |   |                         |  |   |

Heatsinks for D PAK  
Heatsinks for transistors  
Silicone wafers  
Mica wafers

→ C 17  
→ C 4 - 9  
→ E 2 - 4  
→ E 11

Technical introduction  
U-shaped heatsink  
Aluminium oxide wafers  
Kapton insulator washers

→ A 2 - 7  
→ A 117 - 120  
→ E 9 - 10  
→ E 8

**C 10**