

## Attachable heatsink

- universal clip on heatsinks for type TO 218, TO 229, TO 247, TO 248, SIP-Muliwatt and similar
- easy assembly by pushing the heatsink onto the component
- for vertical and horizontal fastening by soldering
- fin height variations on request
- special design accord. to customized specification

<b>art. no.</b>		<b>20,2 K/W</b>			
<b>FK 245 MI 247 O</b>	without soldering lug				
<b>art. no.</b>		<b>20,5 K/W</b>			
<b>FK 245 MI 247 H</b>	with soldering lug for horizontal mounting				
<b>art. no.</b>		<b>19,7 K/W</b>			
<b>FK 245 MI 247 V</b>	with soldering lug for vertical mounting				
<b>art. no.</b>		<b>18,4 K/W</b>			
<b>FK 243 MI 247 O</b>	without soldering lug				
<b>art. no.</b>		<b>19 K/W</b>			
<b>FK 243 MI 247 H</b>	with soldering lug for horizontal mounting				
<b>art. no.</b>		<b>18,4 K/W</b>			
<b>FK 243 MI 247 V</b>	with soldering lug for vertical mounting				

**material:** copper (Cu)  
**material thickness:** 0.6 mm  
**surface treatment:** solderable

**Solder pins** → E 33  
**Solder terminals** → E 32  
**Plugs** → E 33  
**Thermal conductive material** → E 2 - 14

**Heatsinks for D PAK** → C 17  
**Finger-shaped heatsinks** → C 2 - 3  
**Heatsinks for TO 5 and TO 18** → C 15 - 16  
**Heatsinks for transistors** → C 4 - 9

**C 12**

A

B

C

D

E

F

G

H

I

K

L

M

N