

SPECIFICATION

Product : Thermoelectric module

Part Number : PK2-19808NC

1 . Scope

- 1—1 This specification is applied to Multicomp thermoelectric modules
- 1—2 Revision of these specifications is carried out after consent.

2 . Specification

2 - 1 Parameters

Parameters			Remarks
Internal resistance	1.65 Ω \pm 10%		Note-1
I _{max.}	8.5 A		Note-2
V _{max.}	16.1 V		Note-3
	Th=27°C	Th=27°C	
Q _{max.}	51.6 W	51.6 W	Note-4
Δ T _{max.}	85°C	85°C	Note-5
solder melting point	235 °C		Note-6
Maximum. compress.	1MPa		Note-7

Note-1 Measured by AC 4-terminal method at 25°C.

Note-2 Maximum current at Δ T_{max.}

Note-3 Maximum voltage at Δ T_{max.}

Note-4 Maximum cooling capacity at I_{max.},V_{max.} and Δ T = 0°C.

Note-5 Maximum temperature difference at I_{max.},V_{max.} and Q = 0W.

(Maximum parameters are measured in a vacuum 1.3P)

Note-6 The solder melting point of thermoelectric module

Note-7 Recommended maximum compression (not destruction limit)



2 - 2 Outline Drawing