The High Performance Kapton®-Based Insulator

Features and Benefits

- Thermal impedance: 0.41°C-in²/W (@50 psi)
- Tough dielectric barrier against cut-through
- · High performance film
- Designed to replace ceramic insulators



Sil-Pad K-10 is a high performance insulator. It combines special film with a filled silicone rubber. The result is a product with good cut-through properties and excellent thermal performance.

Sil-Pad K-10 is designed to replace ceramic insulators such as Beryllium Oxide, Boron Nitride, and Alumina. Ceramic insulators are expensive and they break easily. Sil-Pad K-10 eliminates breakage and costs much less than ceramics.

TYPICAL PRO	OPERTI	ES OF	SIL-PA	D K-10		
PROPERTY	IMPERIAL VALUE		METRIC VALUE		TEST METHOD	
Color	Beige		Beige		Visual	
Reinforcement Carrier	Kapton		Kapton		_	
Thickness (inch) / (mm)	0.006		0.152		ASTM D374	
Hardness (Shore A)	90		90		ASTM D2240	
Breaking Strength (lbs/inch) / (kN/m)	30		5		ASTM D1458	
Elongation (%45° to Warp and Fill)	40		40		ASTM D412	
Tensile Strength (psi) / (MPa)	5000		34		ASTM D412	
Continuous Use Temp (°F) / (°C)	-76 to 356		-60 to 180		_	
ELECTRICAL						
Dielectric Breakdown Voltage (Vac)	6000		6000		ASTM D149	
Dielectric Constant (1000 Hz)	3.7		3.7		ASTM D150	
Volume Resistivity (Ohm-meter)	1012		1012		ASTM D257	
Flame Rating	VTM-O		VTM-O		U.L.94	
THERMAL						
Thermal Conductivity (W/m-K)	1.3		1.3		ASTM D5470	
THERMAL PERFORMANCE vs PRESS	SURE					
Press	sure (psi)	10	25	50	100	200
TO-220 Thermal Performance (°C/W) 2.3		2.35	2.19	2.01	1.87	1.76
Thermal Impedance (°C-in²/W) (1) 0.8		0.86	0.56	0.41	0.29	0.24

values are provided for reference only. Actual application performance is directly related to the surface roughness, flatness and

Typical Applications Include:

- Power supplies
- Motor controls
- Power semiconductors
- U.L. File Number E59150
- FSCM Number 55285
- Military Specifications
- MIL-M-38527/8A
- MIL-M-38527C
- MIL-I-49456
- MIL-M-87111

Configurations Available:

- Sheet form, die-cut parts, and roll form
- With or without pressure sensitive adhesive

Building a Part Number

Standard Options 44 example Section E NA = Selected standard option. If not selecting a standard option, insert company name, drawing number, and Δ revision level. $_{-2}$ = Standard configuration dash number, 1212 = 12" x 12" sheets, 12/250 = 12" x 250' rolls, or 00 = custom configuration AC = Adhesive, one side 00 = No adhesive Standard thicknesses available: 0.006" SPK10 = Sil-Pad K10 Material

Note: To build a part number, visit our website at www.bergquistcompany.com.

Sil-Pad®: U.S. Patents 4,574,879; 4,602,125; 4,602,678; 4,685,987; 4,842,911 and others.

Kapton® is a registered trademark of DuPont.



www.bergquistcompany.com

The Bergquist Company -The Bergquist Company - Europe Bramenberg 9a, 3755 BT Eemnes Netherlands Phone: 31-35-5380684 Fax: 31-35-5380295 North American Headquarters 18930 West 78th Street Chanhassen, MN 55317 Phone: 800-347-4572 Fax: 952-835-0430

The Bergquist Company - China Rm. 7C, Aihe Mansion No. 629 Ling Ling Road Shanghai, China 200030 Ph: 86-21-6464-2206 Fax: 86-21-6464-2209

All statements, technical information and recommendations herein are based on tests we believe to be reliable, and THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED. INCLUDING THE IMPLIED WARRANTIES OF MARKETABILITY AND FITNESS FOR PURPOSE. Sellers' and manufacturers' only obligation shall be to replace such quantity of the product proved to be defective. Before using user shall determine the suitability of the product for its intended use, and the user assumes all risks and liability whatsoever in connection therewith. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT. INCIDENTAL, OR CONSEQUENTIAL, INCLUDING LOSS OF PROFITS OR REVENUE ARISING OUT OF THE USE OR THE INABILITY TO USE A PRODUCT. No statement, purchase order or recommendations by seller or purchaser not contained herein shall have any force or effect unless in an agreement signed by the officers of the seller PDS_I0043_SP_KI0_0305