



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG



REVISIONS

DOC. NO. SPC-F005 \* Effective: 7/8/02 \* DCP No. 1399

| DCP # | REV | DESCRIPTION          | DRAWN | DATE     | CHECKED | DATE     | APPRVD | DATE     |
|-------|-----|----------------------|-------|----------|---------|----------|--------|----------|
| XX    | XX  | XXXX                 | XXXX  | 13-08-08 | XXXX    | 13-08-08 | XXXX   | 13-08-08 |
| 2067  | B   | Listing Info Updated | JN    | 08-14-09 | JN      | 08-14-09 | JN     | 08-14-09 |

**MATERIAL**

- 2-1. Frame : Thermoplastic PBT of UL 94V-0
- 2-2. Impeller : Thermoplastic PBT of UL 94V-0
- 2-3. Bobbin : Thermoplastic PBT of UL 94V-0
- 2-4. Lead Wire : UL1007, 26 awg, +RED, -BLACK



- 1. Air Flow Direction : Towards label side.
- 2. Best Mounting Direction: Any orientation.

Units:mm



DISCLAIMER:  
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

|              |          |
|--------------|----------|
| DRAWN BY:    | DATE:    |
| XXXX         | 13-08-08 |
| CHECKED BY:  | DATE:    |
| XXXX         | 13-08-08 |
| APPROVED BY: | DATE:    |
| XXXX         | 13-08-08 |

DRAWING TITLE:

DC BRUSHLESS FAN

|            |                     |                 |     |
|------------|---------------------|-----------------|-----|
| SIZE       | DWG. NO.            | ELECTRONIC FILE | REV |
| A          | MC21692             | 14M9048         |     |
| SCALE: NTS | U.O.M.: INCHES [mm] | SHEET: 1 OF 4   |     |

### CHARACTERISTICS

- |                                 |   |   |
|---------------------------------|---|---|
| 1. Motor Design                 | : | DC brushless 4 pole motor design.   |
| 2. Insulation Resistance        | : | More than 10M ohm between internal stator and lead wire(+) measured at DC 500V.   |
| 3. Dielectric Strength          | : | Applied AC 500V for one minute or AC 600V for 2 seconds between housing and lead wire (+)   |
| 4. Noise Level                  | : | Measured in a semi-anechoic chamber with background noise level below 15 dB(A).The fan is running in free air with the microphone at a distance of one meter from the fan intake. |
| 5. Input Power, Current & Speed | : | Measured after continuous 10 minute operation at rated voltage in clean air, and at ambient temperature of 25 degree C.   |
| 6. Tolerance                    | : | ±15% on rated power and current.  |
| 7. Air Performance              | : | Measured by a double chamber. The values are recorded when the fan speed has stabilized at rated voltage.   |



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SIZE DWG. NO.

A

MC21692

ELECTRONIC FILE

14M9048

REV

SPC-F005.DWG


DOC. NO. SPC-F005 \* Effective: 7/8/02 \* DCP No: 1398

SCALE: NTS

U.O.M.: Millimeters

SHEET: 2 OF 4

### PERFORMANCE CURVES



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SIZE DWG. NO.

A

MC21692

ELECTRONIC FILE

14M9048

REV

SPC-F005.DWG

DOC. NO. SPC-F005 \* Effective: 7/8/02 \* DCP No: 1398

SCALE: NTS

U.O.M.: Millimeters

SHEET: 3 OF 4

### SPECIFICATIONS

|                               |   |   |
|-------------------------------|---|---|
| 1-1. Rated Voltage            | : | 24 VDC  |
| 1-2. Operating Voltage Range  | : | 10~27.6 VDC   |
| 1-3. Starting Voltage         | : | 10 VDC (25 deg. C POWER ON/OFF)   |
| 1-4 Rated Speed               | : | 8000 RPM $\pm$ 10%  |
| 1-5. Air Delivery             | : | 56.5 CFM  |
| 1-6. Static Pressure          | : | 0.92 Inch-H <sub>2</sub> O  |
| 1-7. Rated Current            | : | 0.43 AMP  |
| 1-8. Rated Power              | : | 10.3 WATTS  |
| 1-9. Noise Level              | : | 56 dB(A)  |
| 1-10. Direction of Rotation   | : | Counter-clockwise viewed front of fan blade   |
| 1-11. Operating Temperature   | : | -10 to +70 deg. C   |
| 1-12. Storage Temperature     | : | -40 to +70 deg. C   |
| 1-13. Bearing System          | : | Precision ball bearing system   |
| 1-14. Weight                  | : | 90g   |
| 1-15. Safety                  | : | UL/CUR Approvals  |
| 1-16. Vibration               | : | Vibration of acceleration 1.5G and frequency 5~50~5Hz is applied in all 3 directions(X,Y,Z), in cycles of 1 minute each, for a total vibration time of 30 minutes.  |
| 1-17. Locked Rotor Protection | : | Automatic Restart Capacity<br>Note: In a situation where the fan is locked by a external force while the electricity is on, an increase in coil temperature will be prevented by temporarily turning off the electrical power to the motor. The fan will automatically restart when the locked rotor condition is released. |



|   |                  |                            |                                   |               |
|---|------------------|----------------------------|-----------------------------------|---------------|
| ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. | SIZE<br><b>A</b> | DWG. NO.<br><b>MC21692</b> | ELECTRONIC FILE<br><b>14M9048</b> | REV           |
| SPC-F005.DWG  | SCALE: NTS       |                            | U.O.M.: Millimeters               | SHEET: 4 OF 4 |