Mounting Brackets

Option 2: Locking

Cocked connections


P Vertical hanging / standing travels

Extreme accelerations

Corrosion-resistant

If the 1st chain link must pivot

Gliding applications



2....2PZB Fixed end

90°



| 2 | 21PZ | 12/90° | | 22PZB | 17 1 | 5 | |
|--------|----------------|---------------------|---|--------|------|----|--------|
| | 5. | | | 5 | | 10 | |
| Ba + 1 | < _ | 30 <u>t = 7</u> 6.1 | - | 30 | | | Ba - 3 |
| | 2,1 | 3,5 | | 1,5 | | | |
| | . ² | 10 40 | | 40 | 8 | 2 | |

| O | L D . I M | L De a Me | L Deat Ma | Dimension | |
|----------------|----------------|----------------|-------------|-----------|--|
| Chain Type | Part No. | Part No. | Part No. | Dimension | |
| | Full Set | with Tiewrap | Mounting | A in mm | |
| | with | Plates and 10 | Bracket Set | | |
| | Tiewrap Plates | Cable Tiewraps | | | |
| | | | | | |
| 200/240/250.02 | 2020.12PZB | 2020.12PZBK1 | 2020,12PZ | 12 | |
| 200/240/250.03 | 2030.12PZB | 2030.12PZBK1 | 2030.12PZ | 25 | |
| 200/240/250.05 | 2050.12PZB | 2050.12PZBK1 | 2050.12PZ | 44 | |
| 200/240/250.07 | 2070.12PZB | 2070.12PZBK1 | 2070.12PZ | 64 | |
| 200/240/250.09 | 2090.12PZB | 2090.12PZBK1 | 2090.12PZ | 77 | |
| 200/240/250.10 | 2100.12PZB | 2100.12PZBK1 | 2100.12PZ | 90 | |
| 200/240/250.12 | 2125.12PZB | 2125.12PZBK1 | 2125.12PZ | 112 | |

2...12 PZB = Full set, each part with pin/bore, including tiewrap plates

2...1 PZB = Mounting bracket with bore, including tiewrap plates

2...2 PZB = Mounting bracket with pin, including tiewrap plates

