

	ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.			REVISIONS	DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398					
		DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		911	В	Updated & redrawn	JWM	11/15/00	JC	12/6/00	DJC	12/6/00
	SPC-F005.DWG	1385	С	Lid label was KL-9	JWM	11/18/02	JC	11/19/02	JC	11/19/02

HSS-48 HEX 3/16 L2968H 1 907 25 HSS-68 HEX 1/F ToF R/AD, 6 L2969H 1 077 50 # HSS-88 HEX 3/F HSS-88 HEX 3/F L2967H 1 97 25 \*

ſ Ð

6

12

18

## **Bill Of Material**

		• •					7	<u>,</u>	· · · ·	_
	Bill Of Mat	erial			/41.141	ERLOŘ	SPACER AS			
20	KIT LID LABEL	KL-23N3613	1			,	8404	-HSS	,	
э	TRANSPARENT STORAGE BOX	8537-0708	1	(20)	AMERI			XP-4-250 RP-4-500 RP-1   1/4*00 1/4*00 1   1/4*00 1/4*00 1   1/4*00 1/4*00 1   1/4*00 1/4*00 1   1/4*00 1/4*00 1   1/4*00 1/4*00 1   1/4*00 1/4*00 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1 1   1/4*00 1	ROMO HEX 3/16" HE	SS-46 DX 3/16 V/MD, 4
3	HEX SPACER 3/8" LENGTH 1"	HSS-88	25		KEEP YOU			0 6 250 50 6 600 50	алн з/и* алу so алу so * -6-750 HSS-64 HS	q¶rso ¥ SS−66
7	HEX SPACER 3/8" LENGTH 3/4"	HSS-86	25					1/4" 00 1/4" 00 1/4" 00 1/4" 00 1   1/4" 00 1/4" 00 1/4" 00 1   DAMARCE - 0.05444425 - 0.15   NASE - 10.2644425 - 0.15   NASE - 10.2644425 - 0.15   NASE - 10.2644425 - 0.15   SASTH 1/4" 1000011 1/2" 100 -   GTY 30 - - 0.15 -	/**** 10* 10/ 10 10*	EX 1/4" R/HO. 6 NUTH 3/4" QTY 50
6	HEX SPACER 3/8" LENGTH 5/8"	HSS-85	25		applications including industries. This is a pisatics. CPVC has easo	good substitute for metals and n dient corrector resistance to a w	ioni expansive engineering f de range of alkalies and	RP-8-500 RP-8-750 RP- rouse rouse 1/4* ce	8-1000 HSS-85 HS HOMO HCX 3/4" H	* SS-86 EX 3/6*
5	ROUND SPACER #4 LENGTH 1"	RP-8-1000	50		acids. When high te heat deflection tem CPVC is rated has good dielectric	mperature applications are require perature than PVC. as self-extinguishing and sill not properties.	support combustion. It	LOWINCE - CLEMINICE - CLE NO.8 H0.8 H LOWIN 1/2" LOWIN 3/4" LE GY 50 GY 50 Fastic Teaco cutting scale eccou	KLA LONCH 5/8" LEN	N/NC. 8 NOTH 3/47 OTY 25 *
4	ROUND SPACER #4 LENGTH 3/4"	RP-8-750	50				-			
3	ROUND SPACER #4 LENGTH 1/2"	RP-8-500	50				•			
2	HEX SPACER 1/4" LENGTH 1"	HSS-68	50					-		-
	HEX SPACER 1/4" LENGTH 3/4"	HSS-66	50	(			) L	, D	î	<u>_</u>
,	HEX SPACER 1/4" LENGTH 1/2"	HSS-64	50							
	ROUND SPACER #6 LENGTH 3/4"	RP-6-750	50		1	2	3	4	5	
Ī	ROUND SPACER #6 LENGTH 1/2"	RP-6-500	50		-	$\sim$				
	ROUND SPACER #6 LENGTH 1/4"	RP-6-250	50							+
	HEX SPACER 3/16" LENGTH 1"	HSS-48	25		~	_				
	HEX SPACER 3/16" LENGTH 3/4"	HSS-46	50		7	8	9	10	11	
ł	HEX SPACER 3/16" LENGTH 1/2"	HSS-44	50							
3	ROUND SPACER #4 LENGTH 3/4"	RP-4-750	50							
2	ROUND SPACER #4 LENGTH 1/2"	RP-4-500	50		13	14	15	16	17	
	ROUND SPACER #4 LENGTH 1/4"	RP-4-250	50			* *	10	10	·	
м	DESCRIPTION	PART NUMBER	QTY	(19)	<u></u>	NOTE:	KIT LID			

DISCLAIMER:	TOLERANCES:	DRAWN BY:	DATE:	DRAW	ING TITLE:					
LL STATEMENTS AND TECHNICAL INFORMATION CONTAINED	UNLESS OTHERWISE				CPVC Spacer Assortment Kit					
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE	SPECIFIED,	CHECKED BY:	DATE:	SIZE	DWG. NO.		ELEC	TRONIC FILE	REV	
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT	DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.				A 8404-HSS			23N3613.dwg		
FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.		APPROVED BY:	DATE:	$\vdash$						
				SCAL	E: NTS	U.O.M.: INCHES [mm]		SHEET: 1 OF	1	