

PRODUCT DATASHEET

2D Mine Safety Light **Energizer**

INDUSTRIAL+

1259

EXPLOSION-PROOF

- Will not cause an explosion in certain ignitable gas-air and dust-air atmospheres*



BRIGHT

- 9-lumen light output



RELIABLE

- Light for 21 hours of continuous use with Energizer® MAX® D batteries
- Lifetime guarantee



NON-CONDUCTIVE

- Protects user from immediate electric shock



MSHA approved for use in methane-air mixture and UL listed for Division I and II, Class I, Group C and D environments. *For use in gas-air mixtures of Acetone, Butane, Benzene, Diethyl Ether, Ethyl and methyl Alcohols, Gasoline, Methane (natural gas), Naphtha and Propane. Approved also for use in dust-air mixtures of Class II, Group G. Designed so that if lamp is broken, electrical circuit will be opened before filament can ignite these flammable or explosive gas-air mixtures in the surrounding atmosphere.




WARNING:
USE ONLY PR-3 AND 2 SIZE "D" 1.5 VOLT CARBON ZINC BATTERIES.
RISK OF EXPLOSION – DO NOT OPEN IN HAZARDOUS AREA. TO PREVENT THE IGNITION OF A HAZARDOUS ATMOSPHERE, BATTERIES MUST ONLY BE CHANGED IN AN AREA KNOWN TO BE NON-HAZARDOUS.

Before Using Your Flashlight:
Please read all instructions and cautionary markings on the package and light

Product Detail:

Designation: Energizer Industrial 2D Mine Safety Light
Model: 1259
Color: Safety Orange
Power Source: Two "D"
ANSI/NEDA: Series 13
Lamp: PR-3 Krypton
Lamp Rating: 3.6V, 0.5A
Lamp Life (hr): 15
Lamp Output (lumens): 9
Beam Distance (m): 40
Peak Beam Intensity (cd): 400
Run Time (h:mm): 21
Typical Weight: 113 grams without batteries
Dimensions (mm): 203 x 60

Performance:



Tested according to ANSI/NEMA FL 1 Standards.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication
Contents herein do not constitute a warranty
©Energizer / All Rights Reserved