


SAFETY ISOLATING TRANSFORMER


POWER : 1.5VA
 INPUT VOLTAGE : 230V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 2x6V

INHERENTLY SHORT CIRCUIT PROOF TRANSFORMER
 IP00
 UL94V0
 OPERATING TEMPERATURE : -25°C to 70°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 INHERENT PROTECTION

STANDARDS :
 UL506 (File E111078)
 CSA 22-2 (File E111078)
 UL1585 (File E240724)
 VDE (File Ref:1398300)
 EN60950 (File Ref:1398300)
 EN61558-1 (File Ref:1398300)
 EN61558-2-6 (File Ref:1398300)
 CE



N°31



Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matériau:		
Material:			
Dessiné par: ROUSSEL.Ch	Date: 26/05/2004	Visa:	J.P.M.
DATA SHEET 44091			
EI 30x12.5			
		22 Allée du Clos des Chormes Z.A. Les Forges de la Forêt 77390 COLLESEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44091	

D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	