

SAFETY ISOLATING TRANSFORMER





POWER : 5VA
 INPUT VOLTAGE : 230V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 24V

NON SHORT CIRCUIT PROOF TRANSFORMER

IPO0
 UL94V0
 OPERATING TEMPERATURE : -25°C to 50°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 REQUIRED PROTECTION : 200mA FUSE ON SECONDARY

STANDARDS :

- UL506 (File E111078)
- CSA 22-2 (File E111078)
- VDE (File Ref:1398300)
- EN60950 (File Ref:1398300)
- EN61558-1 (File Ref:1398300)
- EN61558-2-6 (File Ref:1398300)
- CE



D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matère:		
Material:			
Dessiné par: ROUSSEL.Ch	Date: 27/09/2005	Visa:	J.P.M.
DATA SHEET 44234			
EI 42x14.8			
		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77390 COLLESEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44234	