





SAFETY ISOLATING TRANSFORMER

POWER : 16VA
 INPUT VOLTAGE : 230V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 6V

NON SHORT CIRCUIT PROOF TRANSFORMER
 IP00
 UL94V0

OPERATING TEMPERATURE : -25°C to 50°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 REQUIRED PROTECTION : 2.5A FUSE ON SECONDARY

- STANDARDS :
- UL506 (File E111078)
 - CSA 22-2 (File E111078)
 - VDE (File Ref:1398300)
 - EN60950 (File Ref:1398300)
 - EN61558-1 (File Ref:1398300)
 - EN61558-2-6 (File Ref:1398300)
 - CE



Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matéria:		
Material:			
Dessiné par: ROUSSEL.Ch	Date: 12/02/2003	Visa:	J.P.M.
DATA SHEET 44301			
EI 54x18.8			
		22 Allée du Clos des Chormes Z.A. Les Portes de la Forêt 77390 COLLESEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44301	

D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	