





**SAFETY ISOLATING TRANSFORMER**

POWER : 16VA  
 INPUT VOLTAGE : 230V  
 FREQUENCY : 50/60Hz  
 NOMINAL OUTPUT VOLTAGE : 12V

NON SHORT CIRCUIT PROOF TRANSFORMER  
 IP00  
 UL94V0

OPERATING TEMPERATURE : -25°C to 50°C  
 STORAGE TEMPERATURE : -25°C to 85°C  
 INSULATION CLASS (IEC85) : B  
 REQUIRED PROTECTION : 1.25A FUSE ON SECONDARY

- STANDARDS :
- UL506 (File E111078)
  - CSA 22-2 (File E111078)
  - VDE (File Ref:1398300)
  - EN60950 (File Ref:1398300)
  - EN61558-1 (File Ref:1398300)
  - EN61558-2-6 (File Ref:1398300)
  - CE



D					
C					
B					
A					
Rev	Date	Modification	Dessiné	Visa	

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matéria:		
Material:			
Dessiné par: ROUSSEL.Ch	Date: 12/02/2003	Visa: J.P.M.	
<b>DATA SHEET 44303</b>			
<b>EI 54x18.8</b>			
		22 Allée du Clos des Chormes Z.A. Les Portes de la Forêt 77390 COLLESEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		<b>DS44303</b>	