



ISOLATING TRANSFORMER

POWER : 1VA
 INPUT VOLTAGE : 230V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 2x24V


INHERENTLY SHORT CIRCUIT PROOF TRANSFORMER
 IP00
 UL94V0
 OPERATING TEMPERATURE : -25°C to 70°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 INHERENT PROTECTION

STANDARDS :
 UL506 (File E111078)
 CSA 22-2 (File E111078)
 CE

CONFORM TO :
 EN61558-1
 EN61558-2-4



<p>44060 230V 50/60Hz (1-5) 24V 0.5VA (6-7) 24V 0.5VA (9-10) ta 70/B</p>	<p>N°23 CE Conform to 61558-2-4 www.myrra.com</p>
-------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------



Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matériau:		
Material:			
Dessiné par: ROUSSEL.Ch	Date: 17/05/2004	Visa:	J.P.M.
DATA SHEET 44060			
EI 30x10.5			
		22 Allée du Clos des Charmes Z.A. Les Forêts de la Forêt 77390 COLLESEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44060	

Rev	Date	Modification	Dessiné	Visa
D				
C				
B				
A				