


ARTWORK INFORMATION

Artwork #: OH-8500-5087
34#: 34-7042-2323-8
Supersedes: OH-8500-3828
Author: KA (3291)
Date: 5/28/98
Structure: Manual 4" x 5.25"



Scale=1 inch



All copy and graphics
print black.

Output at 100%

3M APPROVALS:

3/19/98 3M Packaging Preview, St. Paul
4/02/98 3M Electronic Routing, St. Paul
5/08/98 Westgate/Lee, 3M Canada
5/08/98 N. Lamarche, 3M Montreal
5/06/98 F. Cruz, 3M Mexico
5/07/98 M.C. León, 3M Colombia
5/07/98 E. Guterman, 3M Brazil
4/02/98 3M Final Approval, St. Paul

3M

Occupational Health and Environmental Safety Division

3M Center, Building 275-6W-01
P.O. Box 33275
St. Paul, MN 55133-3275

Occupational Health and Environmental Safety Division

3M Canada Company
P.O. Box 5757
London, Ontario N6A 4T1

Division des produits d'hygiène industrielle et de sécurité environnementale de 3M

Compagnie 3M Canada
C.P. 5757
London (Ontario) N6A 4T1

**Imported by/Importado por:
3M México S.A. de C.V.**

Calz. San Juan de Aragón 516
México, D.F. 07070
RFC TMM-720509 PYA

**Importado 3M/USA, distribuido por:
3M do Brasil Ltda.**

Via Anhanguera, km 110 - Sumaré - S.P.
C.G.C. 45-985.371/0001-08

USA Patents: U.S. PAT. 5,062,421
Brevets américains : U.S. PAT. 5,062,421
E.U.A. Patents: U.S. PAT. 5,062,421
EUA Patents: U.S. PAT. 5,062,421



*Printed on 50% recycled waste paper,
including 10% post-consumer waste paper.*
Printed in the USA.

*Imprimé sur du papier recyclé à 50 %
contenant 10 % de déchets de post-
consommation.*
Imprimé aux États-Unis.

*Impreso en papel reciclado en un 50%,
incluyendo 10% de papel ya usado por los
consumidores.*

Impreso en los Estados Unidos de
América.

*Impresso em papel 50% reciclado de papel
usado, incluindo 10% de papel usado tipo
pós-consumo.*

Impresso nos EUA.

©3M 1998

34-7042-2323-8

3M 6000 Series Half Facepiece Respirator

User Instructions

Respirateurs à demi-masque de série 6000


Directives d'utilisation

Respirador Media Máscara Serie 6000 3M

Instrucciones de uso

Respirador semifacial 3M série 6000

Instruções de uso



Important:

Read and understand all safety information before using.

Important :




Lire et comprendre tous les renseignements relatifs à la sécurité avant d'utiliser le respirateur.

Importante:

Lea y comprenda toda la información sobre seguridad antes de usar un respirador.

Importante:

Leia e compreenda todas as informações de segurança antes de operar.



English

TABLE OF CONTENTS

General Safety Information	2
Use Instructions & Limitations	3
List of Products	7
Assembly Instructions	11
Fitting Instructions	16
Positive & Negative Pressure User Seal Checks	17
Inspection Procedure	22
Cleaning & Storage Instructions	23
3M Limited Warranty	24
3M Worldwide Services Locations	25

For ordering information and location of 3M authorized distributor in your area, call 1-800-328-1667.


For assistance with operation and application of products from 3M Occupational Health and Environmental Safety Division (OH&ESD), please call your 3M representative at 1-800-896-4223 or call 3M Technical Service at 1-800-243-4630. In Canada, call 3M OH&ESD at 1-800-265-1840, extension 6137 or 1-519-452-6137.

**SAVE THIS USER INSTRUCTIONS
AND KEEP IT WITH THE RESPIRATOR.**

GENERAL SAFETY INFORMATION


Intended Use:

The 3M™ 6000 Series Half Facepiece Respirators are designed to help provide respiratory protection against certain airborne contaminants when used in accordance with all use and limitation instructions and applicable safety and health regulations.

	<p>⚠ WARNING</p> <p>This respirator helps protect against certain airborne contaminants. Misuse may result in sickness or death. For proper use, see your supervisor, product packaging or call 3M at 1-800-243-4630. In Canada, call 1 (519) 452-6137 or 1-800-265-1840, ext. 6137.</p>
---	---

<p>⚠ CAUTION</p> <p>Failure to properly dispose of spent cartridges, filters, or respirators contaminated by hazardous materials can result in environmental harm. Handling, transportation and disposal of spent cartridges, filters, or respirators must comply with all applicable federal, state, and local laws and regulations.</p>
--

USE INSTRUCTIONS & LIMITATIONS

	<p>⚠ WARNING</p> <p>This respirator helps protect against certain airborne contaminants. Misuse may result in sickness or death. For proper use, see your supervisor, product packaging or call 3M at 1-800-243-4630. In Canada, call 1 (519) 452-6137 or 1-800-265-1840, ext. 6137.</p>
---	---

Important: Before use the wearer must read and understand these User Instructions. Keep insert for reference.

Use For:

Respiratory protection from certain airborne contaminants according to NIOSH approvals, OSHA limitations, in Canada CSA standard Z94.4-93 requirements, other applicable regulations and 3M instructions.

Do Not Use For:

Concentrations of contaminants which are immediately dangerous to life and health, are unknown or when concentrations exceed 10 times the permissible exposure limit (PEL), when used in air-purifying mode, or according to specific OSHA standards or applicable government regulations, whichever is lower.

Use Instructions:

Failure to follow all instructions and limitations on the use of this respirator and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and may result in sickness or death.

Before occupational use of this respirator a written respiratory protection program must be implemented meeting all the requirements of OSHA 29 CFR 1910.134 such as training and fit testing and applicable OSHA substance specific standards. In Canada, CSA standard Z94.4-93 requirements must be met.

The airborne contaminants which can be dangerous to your health include those that are so small you cannot see them.

Leave contaminated area immediately and contact supervisor if you smell or taste contaminants or if dizziness, irritation, or other distress occurs.

Store respirator away from contaminated areas when not in use.

Dispose of used product in accordance with applicable regulations.

Use Limitations:

This respirator does not supply oxygen when used in air-purifying mode. Do not use in atmospheres containing less than 19.5% oxygen.

Do not use when concentrations of contaminants are immediately dangerous to life and health, are unknown or when concentrations exceed 10 times the permissible exposure limit (PEL) when used in air-purifying mode, or according to specific OSHA standards or applicable government regulations, whichever is lower.

Do not alter, abuse or misuse this respirator.

Do not use with beards or other facial hair or other conditions that prevent a good seal between the face and the faceseal of the respirator.

Time Use Limitations:

If respirator becomes damaged, leave contaminated area and dispose of respirator.

Replace filters in accordance with the filter Time Use Limitation. (See filter *User Instructions*.)

Replace cartridges in accordance with an established change schedule or earlier if smell, taste or irritation from contaminants is detected.

NIOSH Cautions and Limitations:

- A- Not for use in atmospheres containing less than 19.5 percent oxygen when used in air-purifying mode.
- B- Not for use in atmospheres immediately dangerous to life or health.
- C- Do not exceed maximum use concentrations established by regulatory standards.
- D- Air-line respirators can be used only when the respirators are supplied with respirable air meeting the requirements of CGA G-7.1 Grade D or higher quality.
- E- Use only the pressure ranges and hose lengths specified in the table.
- G- If airflow is cut off, switch to filter and/or cartridge and immediately exit to clean air.
- H- Do not wear for protection against organic vapors with poor warning properties or those which generate high heats of reaction with sorbent.
- I- Contains electrical parts which have not been evaluated as an ignition source in flammable or explosive atmospheres by MSHA/NIOSH.

- J- Failure to properly use and maintain this product could result in injury or death.
- L- Follow the manufacturer's instructions for changing cartridges and/or filters.
- M- All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
- N- Never substitute, modify, add or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O- Refer to users instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- P- NIOSH does not evaluate respirators for use as surgical masks.
- S- Special or critical users instructions and/or specific use limitations apply. Refer to instruction manual before donning.


Special Use Instructions:

3M™ Mercury Vapor Cartridges (6009 and 60929) are equipped with passive 3M™ End of Service Life Indicators (ESLI). The color change indicator must be readily visible when wearing the respirator without manipulation. If you cannot readily see the ESLI, do not use.

Mercury vapor cartridges must be discarded when the ESLI changes color; or within 30 days of opening packaging; or when ESLI becomes dirty or damaged; or when odors of vapors or gases become noticeable, whichever occurs first. Mercury vapor has no odor.

LIST OF PRODUCTS

3M™ 6000 Series Reusable Dual Cartridge Respirator



3M™ Facepieces

Half Facepiece assemblies

(minus cartridges, filters, retainers, and prefilters)

6100 small

6200 medium

6300 large

Half Facepiece assemblies

(with probe for quantitative fit testing, includes 2091 P100 filters)

6100Q small

6200Q medium

6300Q large

3M™ Accessories and Parts

200 Voice Projection System - includes 201 microphone adapter

201 Microphone adapter

501 Filter retainer for 5N11 and 5P71 filters

502 Filter adapter for 2000 Series and 7093 filters

504 Respirator cleaning wipes

601 Quantitative fit test adapter

6889 Exhalation valves

6893 Inhalation valves

6895 Inhalation gaskets

3M™ Cartridges

Number	Product Name	NIOSH Approval (for respiratory protection against the following contaminants up to ten times the permissible exposure limit)
6001	Organic Vapor	Certain organic vapors
6002	Acid Gas	Chlorine, hydrogen chloride, and sulfur dioxide or chlorine dioxide or hydrogen sulfide (escape only).
6003	Organic Vapor/ Acid Gas	Certain organic vapors, chlorine, hydrogen chloride, and sulfur dioxide or hydrogen sulfide (escape only) or hydrogen fluoride
6004	Ammonia/ Methylamine	Ammonia and methylamine
6005	*Formaldehyde/ Organic vapor	Formaldehyde and certain organic vapors
6006	*Multi-Gas/Vapor	Certain organic vapors, chlorine, hydrogen chloride, chlorine dioxide, sulfur dioxide, hydrogen sulfide (escape only), ammonia/methylamine, formaldehyde or hydrogen fluoride
6009	Mercury Vapor/ Chlorine Gas	Mercury vapor or chlorine gas
60921	Organic Vapor/P100	Certain organic vapors and particulates
60922	Acid Gas/P100	Chlorine, hydrogen chloride, and sulfur dioxide or chlorine dioxide or hydrogen sulfide (escape only) and particulates
60923	Organic Vapor/ Acid Gas/P100	Certain organic vapors, chlorine, hydrogen chloride, and sulfur dioxide or hydrogen sulfide (escape only) or hydrogen fluoride and particulates
60924	Ammonia/ Methylamine/P100	Ammonia and methylamine and particulates
60925	*Formaldehyde/ Organic vapor/P100	Formaldehyde and certain organic vapors and particulates
60926	*Multi-Gas/ Vapor/P100	Certain organic vapors, chlorine, hydrogen chloride, chlorine dioxide, sulfur dioxide, hydrogen sulfide (escape only), ammonia/methylamine, formaldehyde or hydrogen fluoride and particulates
60929	Mercury Vapor/ Chlorine Gas/P100	Mercury vapor or chlorine gas and particulates

*OSHA regulations require gas proof goggles be worn with half facepiece respirators when used against formaldehyde.

Service Life for 3M™ 6000 Series Cartridges

6000 Series Chemical Cartridges should be used before the expiration date on cartridge packaging. The useful service life of these cartridges will depend upon activity of wearer (breathing rate), specific type, volatility and concentration of contaminants and environmental conditions such as humidity, pressure, and temperature. Cartridges must be replaced in accordance with an established change schedule or earlier if smell, taste or irritation from contaminants is detected.

Special Use Instructions

3M Mercury Vapor Cartridges (6009 and 60929) are equipped with passive End of Service Life Indicators (ESLI). The color change indicator must be readily visible when wearing the respirator without manipulation. If you cannot readily see the ESLI, do not use respirator and do not enter contaminated area. See your supervisor. Mercury vapor cartridges must be discarded when the ESLI changes color; or within 30 days of opening packaging; or when ESLI becomes dirty or damaged; or when odors of vapors or gases become noticeable, whichever occurs first. Mercury vapor has no odor.

3M™ Filters



- 2071 P95 Particulate filter
- 2076HF P95 Particulate/hydrogen fluoride cartridge with nuisance level acid gas relief*
- 2078 P95 Particulate filter with nuisance level acid gas and organic vapor relief*
- 2091 P100 Particulate filter
- 2096 P100 Particulate filter with nuisance level acid gas relief*
- 2097 P100 Particulate filter with nuisance level organic vapor relief*
- 5N11 N95 Particulate filter
- 5P71 P95 Particulate filter
- 7093 P100 Particulate filter

*3M recommended for relief against nuisance levels of acid gas or organic vapors. Nuisance level refers to concentrations not exceeding OSHA PEL or applicable exposure limits, whichever is lower.

ASSEMBLY INSTRUCTIONS


Cartridge Assembly Instructions

1. Align cartridge notch with facepiece mark, as shown, and push together. (Figure 1)
2. Turn cartridge clockwise to stop (1/4 turn). (Figure 2)



Prefilter Assembly Instructions (for 3M™ 5N11 and 5P71 Filters)

1. Place filter into 3M™ 501 Retainer so printed side of filter faces the cartridge. (Figure 3)
2. Press cartridge into filter retainer. It should snap securely into filter retainer. When correctly installed, filter should completely cover face of cartridge.
3. To replace filter, remove retainer by lifting on TAB.





To Attach the 3M™ 2000 Series Filters to the 3M™ 6000 Series Facepiece

Align opening of filter with filter attachment on facepiece. Turn filter clockwise until it is firmly seated and cannot be further turned. Repeat for second filter.

3M™ 502 Adapter Assembly Instructions

1. Align adapter over cartridge. Engage front snap by squeezing front of cartridge and adapter together, placing thumbs of both hands over top of adapter and fingers along bottom sides of cartridge. (Figure 1)



2. Engage back snap by squeezing back side of cartridge and adapter together using the same hand positions. An audible click should be heard as each snap is engaged. The 3M 502 adapter should not be removed or reused once engaged as it is not designed for reuse and leakage may occur. (Figure 2)

To Attach 3M™ 2000 Series Filters to 3M™ 502 Adapter




Place filter onto the filter holder so that filter comes into even contact with gasket. Twist clockwise a quarter turn until it is firmly seated and filter cannot be turned further. Repeat for second filter.

Note:

The 3M 502 adapter once installed on a 3M™ 6000 Series Cartridge is not to be removed and reused as leakage may occur.

Assembly of 3M™ Dual Airline

1. Hold the half facepiece in front of you so that the 3M logo on half facepiece is facing you. Align the two branches of the breathing tube over the two bayonet mounts on half facepiece. For the 3M™ SA-1500 or SA-1600 Breathing Tubes, make sure that 3M logo on breathing tube and on half facepiece are both facing towards you. For 3M™ SA-2500 or SA-2600 breathing tubes, make sure that the 3M logo on breathing tube is facing in opposite direction to 3M logo on half facepieces. (Figure 1) 3M SA-1500 shown
2. Twist each branch of breathing tube clockwise a quarter turn until it is firmly seated in the bayonet and cannot be turned further. Do not forcibly overturn as the bayonet could be damaged. (Figures 2 and 3) 3M SA-1500/SA-1600 breathing tube shown.



Assembly of 3M™ Combination Dual Airline Respirator with Cartridges and Filters

The 3M™ SA-1600 (front-mounted) and SA-2600 (back-mounted) versions of the 3M dual airline breathing tubes allow use of selected, NIOSH-approved 3M™ 6000 Series Cartridges and 2000 Series Filters. For listing of approved cartridges and filters, reference NIOSH approval label included with 3M dual airline breathing tubes. To assemble 3M dual airline breathing tubes with cartridges and/or filters, do the following:

1. Remove the inhalation valves from facepiece and store them so they remain flat. (Figure 1)




Fig. 1




Fig. 2

2. Attach 3M SA-1600 or SA-2600 breathing tubes to facepiece per the procedures outlined previously in this manual. The process is identical to attachment of 3M SA-1500 and SA-2500 models.
3. Make a selection of cartridge and/or filter that meets your respiratory protection requirements, and attach to outer bayonets of 3M SA-1600 or SA-2600 dual airline breathing tubes. (Figure 2)
4. Don facepiece per procedures outlined in fitting instructions.

5. After being properly fit tested, perform a positive and negative user seal check per procedures outlined in seal check instructions. If a proper fit cannot be obtained, see your supervisor. Do not enter contaminated area.
6. Attach an airline to the 3M™ SA-1009 Air Regulator or SA-1029 Low Pressure Connector and adjust air pressure to the specified setting for length of air supply hose employed.

▲ WARNING

If the facepiece is to be used in air purifying mode (without using the 3M SA-1600 or SA-2600 breathing tubes), the inhalation valves must be replaced in the facepiece before use.

Using the 3M™ Combination Dual Airline Breathing Tubes without Cartridges and Filters

To use the 3M combination dual airline breathing tubes (SA-1600 and SA-2600) without cartridges or filters, attach a 3M™ 6880 Bayonet Cap to each outer bayonet mount on the dual airline breathing tube. When used as a straight, Type C, continuous flow supplied air respirator, the Assigned Protection Factor is 50 times the PEL or TLV guidelines for half facepiece respirators.




FITTING INSTRUCTIONS

Must be followed each time respirator is worn

Donning Respirator

1. Place respirator over your mouth and nose, then pull head harness over crown of your head. (Figure 1)
2. Take bottom straps in both hands, place them in back of your neck, and hook them together. (Figure 2)
3. Position facepiece low on the bridge of your nose for optimal visibility and best fit.
4. Adjust top straps first, then lower neck straps by pulling on ends. **DO NOT** pull too tight! (Strap tension may be decreased by pushing out on back side of buckles.) Perform a positive pressure and/or negative pressure user seal check. The positive pressure method is recommended. (Figure 3)

If you cannot achieve a proper fit, **DO NOT** enter contaminated area. See your supervisor.



Quantitative and Qualitative Fit Testing

The effectiveness of a respirator will be reduced if it is not fitted properly. Therefore, either quantitative or qualitative fit testing must be conducted prior to the respirator being issued.

Note:

Fit testing is a U.S. Occupational Safety and Health Administration (OSHA) and Canadian CSA requirement. Quantitative Fit Testing (QNFT) can be conducted using a 3M™ 601 Fit Test Adapter and 42 CFR 84 P100 filters such as the 3M™ 2091 or 7093 Particulate Filters.

Qualitative Fit Testing (QLFT) with the 3M™ FT-10 or FT-30 Qualitative Fit Test Apparatus can be conducted using any of the NIOSH approved 42 CFR 84 particulate filters.

Note:

For further information concerning fit testing contact 3M OH&ESD Technical Service at 1-800-243-4630 or a 3M location in your region as listed in 3M Worldwide Services Locations section later in this manual. In Canada call, 1 (519) 452-6137 or 1-800-265-1840, ext. 6137.

SEAL CHECK FOR 6000 SERIES CARTRIDGES

Always Check the Seal of the Respirator on Your Face Before Entering a Contaminated Area.

Positive Pressure Seal Check

Place the palm of your hand over the exhalation valve cover and exhale gently. If facepiece bulges slightly and no air leaks are detected between your face and the facepiece, a proper fit has been obtained.

If face seal air leakage is detected, reposition respirator on your face and/or readjust tension of the elastic straps to eliminate leakage.

Repeat above steps until a tight face seal is obtained.

If you cannot achieve a proper fit, **DO NOT** enter contaminated area. See your supervisor.



Negative Pressure Seal Check

Place palms of hands to cover face of cartridge or open area of 3M™ 501 Filter Retainer, when retainer is attached to the cartridge, to restrict air flow.

Inhale gently. If you feel facepiece collapse slightly and pull closer to your face with no leaks between the face and facepiece, a proper fit has been obtained.



If face seal air leakage is detected, reposition respirator on face and/or readjust tension of straps to eliminate air leakage. Repeat above steps until a tight face seal is obtained.

If you cannot achieve a proper fit, DO NOT enter contaminated area. See your supervisor.

Note:

Use of 3M 501 filter retainer may aid respirator wearer in conducting a negative pressure seal check.

SEAL CHECK FOR 2000 SERIES FILTERS

Always Check the Seal of the Respirator on Your Face Before Entering a Contaminated Area.

Positive Pressure Seal Check

Place the palm of your hand over the exhalation valve cover and exhale gently. If facepiece bulges slightly and no air leaks are detected between your face and the facepiece, a proper fit has been obtained.

If face seal air leakage is detected, reposition respirator on your face and/or readjust tension of the elastic straps to eliminate leakage.

Repeat above steps until a tight face seal is obtained.

If you cannot achieve a proper fit, DO NOT enter contaminated area. See your supervisor.



Negative Pressure Seal Check


Place your thumbs onto the center portion of the filters, restricting airflow into the breathing tube of filters, and inhale gently.

If you feel facepiece collapse slightly and pull closer to your face with no leaks between the face and facepiece, a proper fit has been obtained.

If face seal air leakage is detected, reposition respirator on face and/or readjust tension of straps to eliminate the leakage.

Repeat above steps until a tight face seal is obtained.


If you cannot achieve a proper fit, DO NOT enter contaminated area. See your supervisor.



INSPECTION PROCEDURE

The 3M™ 6000 Series Respirator must be inspected before each use to ensure that it is in good operating condition. The facepiece should be disposed of upon observation of damaged or defective parts. The following inspection procedure is suggested.


1. Check facepiece for cracks, tears and dirt. Be certain facepiece, especially face seal area, is not distorted.
2. Examine inhalation valves for signs of distortion, cracking or tearing.
3. Make sure that head straps are intact and have good elasticity.
4. Examine all plastic parts for signs of cracking or fatiguing. Make sure filter gaskets are properly seated and in good condition.
5. Remove exhalation valve cover and examine exhalation valve and valve seat for signs of dirt, distortion, cracking or tearing. Replace exhalation valve cover.



CLEANING AND STORAGE INSTRUCTIONS

Cleaning is recommended after each use.

1. Remove cartridges and/or filters.
2. Clean facepiece (excluding filters and cartridges), with 3M™ 504 Respirator Wipes or by immersing in warm cleaning solution, water temperature not to exceed 120°F, and scrub with soft brush until clean. Add neutral detergent if necessary. Do not use cleaners containing lanolin or other oils.
3. Disinfect facepiece by soaking in a solution of quaternary ammonia disinfectant or sodium hypochloride (1oz. [30ML] household bleach in 2 gallons [7.5L] of water), or other disinfectant.
4. Rinse in fresh, warm water and air dry in noncontaminated atmosphere.
5. Respirator components should be inspected prior to each use. A respirator with any damaged or deteriorated components should be discarded.
6. The cleaned respirator should be stored away from contaminated areas when not in use.



LIMITED WARRANTY

3M warrants to the original purchaser that 3M™ 6000 Series Half Facepiece Respirators and their components are quality products and will be free of defects in materials and workmanship and in conformance with any express warranty for a specific purpose for the first 90 days after delivery to the original purchaser and 3M's only obligation and your exclusive remedy shall be to repair, replace or refund the purchase price of such parts or products upon timely notification thereof and substantiation that the product has been stored, maintained and used in accordance with 3M's written instructions.

EXCLUSIONS TO WARRANTY: THIS WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ANY WARRANTY AND CONDITION, EXPRESS OR IMPLIED, STATED OR OTHERWISE, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHER CONDITION OR WARRANTY OF QUALITY, EXCEPTING WARRANTIES OR CONDITIONS OF TITLE AND AGAINST PATENT INFRINGEMENT.

Limitation of Liability: Except as provided above, 3M shall in no event be liable or responsible whether in contract or in tort or any other legal theory for any injury, loss or damage, direct, indirect, special, incidental or consequential, arising out of the use or misuse or inability to use the equipment. 3M warranties and conditions as herein above set forth shall not be enlarged, diminished or affected by, and no obligation or liability shall arise or grow out of, the rendering of technical advice or service by 3M or its agents. The foregoing may not be changed except by written agreement signed by an authorized officer of 3M. THE REMEDIES SET FORTH HEREIN ARE EXCLUSIVE.

3M WORLDWIDE SERVICES LOCATIONS

Sales Information:
1-800-896-4223
Technical Service Information:
1-800-243-4630

Alaska

3M Alaska Branch
Anchorage
Tel: (907) 522-5200

Argentina

3M Argentina
S.A.C.I.F.I.A.
Provincia de Buenos Aires
Tel: 54-1-469-8200

Australia

3M Australia Pty. Ltd.
Pymble, N.S.W.
Tel: 61-2-9498-9333

Austria

3M Oesterreich Ges M.H.H.
Vienna
Tel: 43-1-866860

Belgium

3M Belgium N.V./S.A.
Diegem
Tel: 32-2-722-5111

Brazil

3M do Brasil Ltda.
Sao Paulo
Tel: 55-19-864-7000

Canada

3M Canada Company
London, Ontario
Tel: 519-451-2500

Chile

3M Chile, S.A.
Santiago
Tel: 56-2-410-3000

China

3M China Limited
Shanghai
Tel: 86-21-6275-3535

Colombia

3M Colombia S.A.
Bogota
Tel: 57-1-416-1655

Costa Rica

3M Costa Rica, S.A.
San Jose
Tel: 506-260-3333

Czech Republic

3M Cesko, Spol. SRO
Czech Republic
Telephone: 422-255-145

Denmark

3M A/S
Glostrup
Tel: 45-43-48-01 00

Dominican Republic

3M Dominicana S.A.
Santo Domingo
Tel: (809) 530-6560

Ecuador

3M Ecuador CA
Guayaquil
Tel: 593-4-800-777

Egypt

3M Egypt Ltd.
Cairo, Egypt
Tel: 202-417-6559

El Salvador

3M El Salvador,
S.A. de C.V.
San Salvador
Tel: (503) 278-3344

Finland

Suomen 3M OY
02630 Espoo
Tel: 358-9-52521

France

3M France
Cergy Pontoise Cedex
Tel: 33-1-30-31-61-61

Germany

3M Deutschland GmbH
Neuss
Tel: 49-2131-140

Greece

3M Hellas, Ltd.
Maroussi, Athens
Tel: 30-1-6842902

Guam

3M Company
Tamuning
Tel: 671-6469161

Guatemala

3M Guatemala, S.A.
Guatemala City
Tel: 502-5911236

Gulf

3M Gulf Ltd.
Dubai
Tel: 971-4-626-160

Hawaii

3M Hawaii
Honolulu
Tel: (808) 422-2721

Honduras

Honduras Branch
San Pedro Sula
Tel: 504-52-8176

Hong Kong

3M Hong Kong Limited
Hong Kong
Tel: 852-2806-6111

Hungary

3M Hungaria Kft.
Budapest
Tel: 36-1-267-1680

India

Birla 3M Limited
Bangalore
Tel: 91-80-5588881

Indonesia

PT. 3M Indonesia
Jakarta
Tel: 62-21-5212166

Ireland

3M Ireland – 3M House
Co. Dublin
Tel: 353-1-2803555

Israel

3M Israel Ltd.
Herzliya Indl Zone
Tel: 972-9-9561490

Italy

3M Italia SPA
Milano
Tel: 39-2-70351

Jamaica

3M Interamerica, Inc.
Kingston
Tel: 809/937-3859-65

Japan

3M Health Care, Ltd.
Setagaya-ku, Tokyo
Tel: 81-3-3709-8111

Kenya

3M Kenya Ltd.
Nairobi
Tel: 254-2-560-712

Korea

3M Korea Ltd.
Seoul 150-010
Tel: 82-2-3771-4114

Malaysia

3M Malaysia Sdn. Berhad
Kuala Lumpur
Tel: 603-775-7555

Mexico

3M México, S.A. de C.V.
México
Tel: 52-5-626-0400

Morocco

3M Maroc
Casablanca, Maroc
Tel: 212-2-984965

Netherlands

3M Nederland B.V.
The Netherlands
Tel: 31-71-5-450-450

New Zealand

3M New Zealand Ltd.
Auckland
Tel: 64-9-444-4760

Norway

3M Norge A/S
Skjetten
Tel: 47-63-84-75-00

Pakistan

3M Pakistan (PVT) Limited
Karachi
Tel: 92-21-5611901

Panama

3M Panama S.A.
Panama 5
Tel: 507-263-5244

Peru

3M Peru, S.A.
Lima
Tel: 51-1-2242728

Philippines

3M Philippines, Inc.
Makati, Metro Manila
Tel: 63-2-813-3781

Poland

3M Poland SP. ZO.O.
Warszawa, Poland
Tel: 48-22-6328815

Portugal

Minn. (3M) de Portugal, Lda.
Lisbon
Tel: 351-1-313-4500

Puerto Rico

3M Puerto Rico, Inc.
Carolina
Tel: (787) 750-3000

Russia

3M Russia
Moscow
Tel: 7(095) 288 97 01

Singapore

3M Singapore Pte. Ltd.
Singapore
Tel: 65-454-8611

South Africa

3M South Africa (Pty.) Ltd.
Johannesburg
Tel: 27-11-922-9111

Spain

3M Espana, S.A.
Madrid
Tel: 34-1-321-60-00

Sri Lanka

3M Lanka (Private) Limited
Pelawatte, Battaramulla
Tel: 941-867-891-2

Sweden

3M Svenska AB
Sollentuna
Tel: 46-8-92-2100

Switzerland

3M (Schweiz) AG
Rueschlikon
Tel: 41-1-7249090

Switzerland

3M (East) AG
Rotkreuz
Tel: 41-41-799 40 40

Taiwan

3M Taiwan Limited
Taipei
Tel: 886-2-704-9011

Thailand

3M Thailand Ltd.
Bangkok
Tel: 662-260-8577

Trinidad

3M Interamerica, Inc.
Port of Spain
Tel: 809/623-8917

Turkey

3M Sanayii ve Ticaret A.S.
Istanbul
Tel: 90-212-282-23 82

United Kingdom

3M United Kingdom PLC
Bracknell, Berkshire
Tel: 44-1-344-858000

Uruguay

3M Uruguay S.A.
Montevideo
Tel: 598-2-493-341

Venezuela

3M Manufact. Venezuela S.A.
Caracas
Tel: 58-2-508-8111

Vietnam

3M Vietnam Ltd.
Ho Chi Minh City
Tel: 848-832-366

Zimbabwe

3M Zimbabwe (Pvt) Ltd.
Harare
Tel: 263-4-486384