



## Features:

- Ideal for use by electronic manufacturers working with ESD sensitive components
- Highly visible with yellow header and ESD Protective Symbol allowing people to immediately know the badge holder has ESD control properties
- .024" thick ±10% tolerance on the back and .012" thick ±10% tolerance on the front to ensure durability and high-end appearance
- RTT: 10E6 to 10E10 ohms per ANSI/ESD S11.11
- Tribocharging: Less than 100 volts
- Genuine Made In America accept no substitutes
- Available in horizontal and vertical
- We can do Customs just let us know your insert size!

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20-2008 section 2.4 Sources of Static Electricity]

<u>35010</u>	ESD Badge Holder, Clip-On, Vertical, 2-11/16" x 3-11/16" (OD), 2-3/8" x 3-3/8" (Insert Size)
<u>35011</u>	ESD Badge Holder, Clip-On, Horizontal, 3-7/8" x 2-9/16" (OD), 3-5/8" x 2-3/8" (Insert Size)
<u>35012</u>	ESD Badge Holder, Clip-On, Horizontal, 4-1/4" x 2-15/16" (OD), 3-7/8" x 2-5/8" (Insert Size)
<u>35013</u>	ESD Badge Holder, Clip-On, Horizontal, 4-5/16" x 3-3/8" (OD), 4" x 3" (Insert Size)



## **ESD Dissipative Badge Holder**



3651 WALNUT AVE., CHINO, CA 91710 PHONE: (951) 627-2453 • FAX: (951) 755-8848

WEBSITE: Menda-ID.com

DRAWING NUMBER 35010 DATE: July 2009

© 2009 DESCO INDUSTRIES INC