

**Description:**

Statfree DLR material meets the working surface requirements of EN61340-5-1. This material is a dual purpose rubber matting material. The two layer construction allows it to be used as a dissipative or a conductive matting product. The soft dissipative layer makes an excellent table mat, ideal for use in soldering and assembly areas. This rubber material has superior resistance to heat, abrasion, chemicals, and is easy to clean and maintain. Statfree DLR material will not melt and does not burn when coming into contact with hot metal parts or soldering debris. It is amine, chloride, sulfide, alumina, and magnesia free.

**Specifications:**

Construction: Dual layer Static Dissipative rubber  
 Material Thickness: 2mm (± 5%)  
 Colours: Grey, Blue, Beige  
 Texture: Slight emboss  
 Weight: 2.7kg/m<sup>2</sup>  
 Hardness: 75 ± 5 Shore A  
 Rp-p Colour Layer: 10E6 - 10E8 ohms tested per IEC 61340-2-3  
 Rp-p Black Layer: <10E5 ohms tested per IEC 61340-2-3  
 Rg Colour Layer: 10E6 - 10E8 ohms tested per IEC 61340-2-3  
 Rg Black Layer: <10E5 ohms tested per IEC 61340-2-3

**Grounding:** This material must be properly grounded for optimum electrical performance.

**Cleaning:** Use only ESD mat cleaner such as Reztore™ Surface & Mat Cleaner to clean and extend mat useful life. Do not use cleaners containing silicone as silicone will create an insulative film on the surface. Do not use solvent based cleaners as solvents will dry out matting and may cause curling.

*EN 61340-5-1 paragraph 5.2.2 Working surfaces and storage racks  
 "All working surfaces and storage racks on which unprotected ESDS  
 may be placed shall be capable of being connected to EPA ground and  
 shall have a point-to-point resistance and resistance to EPA ground in  
 accordance with table 1 (Rp greater or equal to 1 x 10E4, less than or  
 equal to 1 x 10E9 ohms, and Rg greater or equal to 7,5 x 10E5 to less  
 than or equal to 1 x 10E9 ohms)."*



Tolerances are ± 5mm unless specified

Special manufactured items are not returnable for credit **MADE IN BRITAIN**

Item #	Farnell #	Size	Colour	Approval
VER-28214	1833422	1.22M x 10M	Blue	
VER-28215	1833423	1.22M x 10M	Grey	
VER-28216	1833424	1.22M x 10M	Beige	

**ROLL, DISSIPATIVE STATFREE DLR RUBBER**

# Vermason

VERMASON  
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,  
 HERTFORDSHIRE, SG6 2TD, UNITED KINGDOM  
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440  
 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

**DRAWING NUMBER**

VER-28214

**DATE**

August  
 2010