



SPECIFICATIONS:

Mat:

- Construction: Dual layer rubber material
 - Static Dissipative top layer
 - Conductive rubber bottom layer

Material Thickness: .060" (± 10%)

Color: Dark Blue

Texture: Smooth

Dissipative Color Side:

- RTT: 10E6 - 10E8 ohms per ANSI/ESD S4.1
- RTG: 10E6 - 10E8 ohms per ANSI/ESD S4.1

"Slows charge removal; meets minimum recommended work surface requirements of ANSI/ESD S20.20 and recommendations of STM 4.1"

Wrist Strap:

Construction: Soft elastic band with silver impregnated polypropylene on the inside for reliable removal of static charge

Snap: 4mm male stud snap

Cord Length: 6'

Cord Terminations: 4mm socket snap, molded banana plug

Ground Cord:

Length: 15'

Terminations: 10mm male stud snap, ring terminal

Resistor: 1 megohm

Universal Snap Kit:

Size: 10mm

Kit Includes: 10mm stud snap, 10mm socket snap, threaded backing washer, long screw, short screw, & groundable point label


PACKAGING:

Product to be packaged with Duratool label



Special manufactured items are not returnable for credit

MADE IN AMERICA



Packaging Label

Tolerances:
Width: ± 0.250"
Length: ± 0.250" every 1 linear foot of running material

<p>CUSTOMER APPROVAL _____ DATE _____</p>	<p>BENCH TOP MAT, 2 LAYER RUBBER, 24" x 48", WRIST STRAP, ADJ ELASTIC, 6' COIL CORD, GROUNDING CORD, UNIVERSAL SNAP KIT, PACK WITH DURATOOL LABEL, MC35759</p>				
<p>CMG</p>	<p>3651 WALNUT AVE., CHINO, CA 91710 PHONE (909) 627-9634 FAX (909) 363-7322 WEBSITE: www.CMG-Sales.com</p> <table border="1" data-bbox="1328 1507 1554 1600"> <tr> <td data-bbox="1328 1507 1451 1562">DRAWING NUMBER</td> <td data-bbox="1451 1507 1554 1562">DATE</td> </tr> <tr> <td data-bbox="1328 1562 1451 1600">CMG-10746</td> <td data-bbox="1451 1562 1554 1600">July 2010</td> </tr> </table>	DRAWING NUMBER	DATE	CMG-10746	July 2010
DRAWING NUMBER	DATE				
CMG-10746	July 2010				