



ESD CONDUCTIVE GRID TAPE

- Polypropylene self adhesive tape with static dissipative surface
- Silicone Free - No Residue
- Beige with Black Conductive Grid & ESD Warning Triangle
- For use with all Static Sensitive Packaging and Sealing Applications

Technical

- Tensile Strength: MD 5.00 Kg / 15mm CD 10.00Kg / 15mm
- Elongation: MD 150% CD 50%
- Resistivity:
- Anti Static Adhesive Co-polymer Layer 1×10^9 Ohms
- Conductive Grid Layer: 10^4 to 10^5 Ohms
- Anti Static Copolymer Layer: 8×10^{12} Ohms
- Charge Decay Time: (FTMS 4046, 101c) 0.01 Seconds
- Thickness: 49 Microns
- Carrier: 28 Microns
- Adhesive: 21 Microns
- Peel Adhesion: 0.45Kg/15mm (minimum)
- Temperature Resistance: 60°C / 140°F (maximum)
- Base Material : OPP
- Adhesive Solvent: Acrylic Base
- Core Size: 3"



PART: PART: 054-0109 - 24mm Width x 40m

Packaging: 1 x Reel 24mm x 40m

Product Data Sheet

Antistat – The ESD Control Centre Limited, 108 Claydon Industrial Pk, Gt Blakenham, Ipswich, Suffolk, UK. Tel: +44 (0) 1473 836 200 Fax: +44 (0) 1473 836 220