

## Laminating Sheets

## Features:

- Our ESD laminating sheets will work with any standard document laminating system found from any office supply stores
- Made from PET / EVA
- 80 micron thickness
- Grammage of 95gram/m<sup>2</sup>
- Elongation: MD161% / TD120



## Specification:

Details	Standard	Typical Value
Surface Resistance Rs	EN 61340-5-1	<10 <sup>9</sup> Ω/sq
Decay Time	EN 61340-5-1	<2 secs

Product Code:	Description:	Size:	Additional Notes:
1822265	ESD Laminating Sheets	A4	Pack of 100 (Ref: 105-0094)

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Famell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual poperty rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Lisens of this data sheets previously supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheets previously supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of its data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2008.

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk

