- Microcontroller development software
- Easy to use graphical interface
- Fast and flexible
- PICmicro and AVR devices













Introduction

Flowcode 3 is one of the World's most advanced graphical programming languages for microcontrollers.

The great advantage of Flowcode is that it allows those with little experience to create complex electronic systems in minutes.

Flowcode achieves this in two steps: firstly students drag and drop flowchart symbols onto the screen, fill in the dialog boxes when prompted. Then Flowcode compiles the flow chart into code that is downloaded to a microcontroller which executes the program.



BENEFITS

- **Save time and money** Flowcode facilitates the rapid design of electronic systems based on microcontrollers.
- **Easy to use interface** Simply drag and drop charts on screen to create a electronic system without writing traditional code line by line.
- **Fast & flexible** Flowcode has a host of high level component subroutines which means rapid system development. The flowchart programming method allows users of all abilities to develop microcontroller programs.
- Error free results Flowcode works. What you design and simulate on screen is the result you get when you download to your microcontroller.
- **Open architecture** Flowcode allows you to view commented C and ASM code for all programs created. Access circuit diagram equivalents to the system you design through our datasheets and support material.
- **Fully supported** Flowcode is supported by a wide range of materials for learning about, and developing, electronic systems.

Flowcode now supports PICmicro, AVR and ARM microcontrollers.

"Flowcode is great for students with no experience at all to get acquainted with electronics and programming in a very fast and fun way." Bart Huyskens

St Joseph's College, Belgium

"The newer Flowcode and E-blocks offer the potential to make the learning of Microprocessor Systems and Electronics far more interesting." Malcom Newton Isle of Man College, UK

dis www.matrixmultimedia.com



The design process

Design

Flowcode contains standard flow chart icons and electronic components that allow you to create a virtual electronic system on screen. Use the drag and drop interface to create a program and click on each icon and component to set the actions and properties you need. The range of components is large and includes simple switches and LEDs, communication bus interfaces like I²C and SPI, and more advanced components such as Bluetooth and internet servers.

- Easy to use interface
- Allows complex systems to be developed and managed quickly
- Supports most PICmicro and Atmel AVR microcontrollers





Once your system is designed you can use Flowcode to simulate it in action. Menu controls allow you to step through each icon in the program and see the effects on the on-screen components, and on microcontroller itself. Test the system's functionality by clicking on switches or altering sensor values, and see how your program manages the changes in the electronic system.

- Simulation aids understanding
- Debug before download
- Shorten the design cycle





...the simulation software shows you the effects on your microcontroller, your components and your flow chart...

Download When you are satisfied with your design click one

button to send the program to your microcontroller device. Flowcode produces standard Hex code for AVR and PlCmicro microcontrollers. Flowcode is directly compatible with the E-blocks range of modular electronics modules.

- Compiles to C then ASM then Hex
- Link in your own C or ASM files
- Immediately download to your programmer



PICmicro and PIC are trademarks of Arizona Microchip Inc. Atmel and AVR are trademarks of the Atmel corporation.



Flowcode users

Flowcode is used in education and industry. Its comprehensive functionality meets the needs of today's technology educators and industrial designers.

Flowcode in industry

Industrial users vary from those just starting to use microcontrollers, to experienced systems engineers using Flowcode for small projects, prototyping, and de-skilling the design process.

- Quick projects: Flowcode is used even by experienced C code programmers because it is the quickest way of getting programs up and running.
- Managing projects: Flowcode is used as a 'front end' to manage complex projects containing C code. This allows engineers to de-skill the design process with one programmer developing core routines and another managing the user interface, ergonomics and program flow.
- Rapid prototyping: the tight integration of E-blocks and Flowcode allows incredibly rapid 'proof of concept' prototypes to be developed for customer surveys and specification development.
- **Open architecture:** The open architecture of E-blocks and Flowcode are designed to save engineers time in the design process: use our off the shelf software component designs with our off the shelf Eblocks hardware components to shorten the design cycle.

Flowcode in education

Educators incorporate Flowcode into their Electronics, Computer Science and Technology courses for many reasons including:

- Fundamentals of programming: Flowcode is an ideal tool for learning the fundamentals of programming. The process of building programs using drag and drop and point and click, allows students to understand program structure and flow without getting bogged down in syntax and language.
- **Fundamentals of electronics** design: in using Flowcode students are introduced to the concepts of system design, of inputs, outputs and processes. Students also learn about microcontroller circuitry and operation.
- A precursor to C: Flowcode is designed as a precursor to C programming which many students find difficult. Flowcode introduces students to the concepts of programming and prepares them for the principles used in C programming.
- **Motivation:** Flowcode allows students to go further, faster, and develop projects which utilise the technology they use every day like mobile phones, MP3 players, GPS etc. Flowcode motivates students to want to learn more about electronic system design.



Flowcode and E-blocks have been adopted by Belgian schools for post 16 education in electronics. Shown here is the electronics teaching lab at St Joseph's Academy near Brecht.

TE-60-4

Downloaded from Elcodis.com electronic components distance www.matrixmultimedia.com



Support

Whether you are in education or industry you will find that there are a wide range of resources available to help gain knowledge on how Flowcode is used, programming concepts, microcontroller techniques and circuits.

- In-package support: Flowcode is shipped with a comprehensive help file covering all Flowcode functions. Over 30 example files are included with full descriptions.
- Free web based courseware: on our web site you will find a number of free web based courseware applications which cover not only how Flowcode is used but also cover the basics of microcontrollers, and how they are used in electronic systems,
- Forums: Online forums are used as a mechanism for building an knowledge base on Flowcode. Our engineers answer all questions on the forums on a daily basis.
- **Tutorial manuals:** for more advanced topics, such as Bluetooth, CAN, and TCP/IP, are available.
- Technical support: as you would expect our engineers provide free technical support for functional problems with Flowcode.







The Flowcode / E-blocks Learning Centre includes several web based tutorials and videos supporting Flowcode users

0 0	BO PARA		
eri 🍓 hetp://www.matri	multimedia condimitionumidiventropic	sheit-136 👻 🖸 Ga	1910
gir •	C Seath + C	S B+blodet & Oek • Aktikk • State & Options	
mim matrix multimedia User forums www.matrixmultimedia.com		Matrix Multimedia user forums For users to discuss using Matrix Multimedia products.	
		Erag Etaarch Efferderliet Etterproups Bagieter. Erroffe Etag in to thesk your private messages Blag in	
MA JIZ III Y	rer s		
🕄 men tapet) 🌘 pa	Hatrix Hultimedia	user forums Forum Index >> flowcode	
ann ()	etreply) Hatrix Hultimedia	user forums Forum Index -> Fluecode View previous topic = View a	iest topic
andhar	itingiy) Hatrix Hultimedia	user forums Forum Index -> Fluecode View previous topic = View a ricesage	est topic
anteringin) () pro- Antibase Langay	Divided: Tue Jul 11, 2006	user farmes Farmes Early > Farecode View previous topic = View p Through 10:17 an . Peet signed: DMX 512 in Yw3	(Tparts)
Author Author Lanjay	Difference in the second secon	View previous fapit: 2 View s View previous fapit: 2 View s (1017 av. Pert adject DMI 12 in Ind bit 512 decoder module into VER3 to interface with t	ent topic (Tiganto) the PIC's
Author Author Lanjay Invest: 11.3.4 2004 Instal: 1 Lack to top	Hatrix Hultiwedia DForted: Tue Jul 11, 2006 He, do you think it would in board UART	Wate Spreads of Handbald Water provinces Royal 2: Water a realization Biol 2 are: First related: RMIN 31 a Water De possible to throw in a DMN 512 decoder module into VER3 to interface with the mail	(C gunt) the PIC's
Anches Anches canjay annadi 11 Jul 2004 Mater 1 lack to top feve	Histrix Hultiwedia Directed: Tue Jul 11, 2006 Hi, do you think it would i on board UART	vaar farmus Farms bake - 5 filmende Vaar previoes Kapit is Vier is Mitsaaa 1012 ar Part Adamt Bills 112 decoder module into VBI 16 interface with t mmi) 2013 m Fast Adamt	C gutte
Author Author Langay Instant 11 Jul 2005 Tastes 11 Jul 2005 Tastes 12 Jul 2006 Tastes 13 Date to post Author Marcel 13 Jun 2006 Tastes 13 Date 13 Jun 2006 Tastes 13 Date 13 Jun 2006	Attris Hallinedia Desnel: Tue Al 11, 2006 H, do you think it would on board UAPT Desnel: Wed Al 12, 2006 I'm afraid I'll have to say want to divert our faired area to say want to divert our faired area.	valer formule if annue taken - of financed Valer provinces. Name 2: Valer is not seen a seen original. Bird: 13.1 a. valo 16.13 ar: Faver radgest. Bird: 15.12 decoder module ento VER3 to interface with th wind? h.28 ar: Faver radgest. '''' to that request. Vale are vary does to releasing a ESTA version of v3 and 1 all the	C guite C guite the PIC's C guite don't sour gen
Auchor Auchor Auchor Annel 13 Jd 2000 Parks 1 Back to top Steve St	Natris Hallimedia Desinter Tus Inf 11, 2005 H, do you think it would no on board UART Desinter Wed Jul 32, 2006 Tim afraid Til have to age Want to divert our efforts Want to divert our efforts Incidentally, v2 Will give y 'C' functions and call these to use the	valer forward Farvais Daliks - O Financed Valer provinces. Name 2: View a network - Name 2: View a 10-13 are - Free release. DRIV, 13.1 n. vec) the possible to throw in a DRIV 53.2 decoder module reto. VEX.1 to interface with t with a - Free release. View are very door to releasing a EXTA version of v3 and 1 at their Related. This To State requests: View are very door to releasing a EXTA version of v3 and 1 at their Related. This To State request. View are very door to releasing a EXTA version of v3 and 1 at their Related.	eet tapic (gunts) te PIC's don't sour own should be

Web based forums, covering a variety of topics, are monitored by our technical support team on a daily basis

Downloaded from <u>Elcodis.com</u> electronic components distance di distance distance distance distance di



Case study - Flowcode in education



Our Internet board is used as part of an E-blocks prototyping system.....



...here is the complete program...

END

Together Flowcode and E-blocks have the capability to provide access to complex electronics systems for those without programming, or electronics design experience. These images show you how.

The system shown here allows students to publish a web page showing the value of a real world sensor - in this case a temperature sensor. Students learn how an embedded internet system can be used for control and monitoring and combine this with Java programming exercises to produce graphs showing temperature over time.

Additional Flowcode subroutines allow students to dig deeper and learn about TCP/IP packet structure, and protocols.



...students click on flowchart icons and set properties of macros as appropriate- including the HTML ...



...the results can be seen at the appropriate IP address using Windows Explorer on a PC.

Details correct at time of going to press. Matrix Multimedia reserves the right to change specification.



Case study - Flowcode in industry

Flowcode's inbuilt library of components, and tight integration with our E-blocks hardware modules, makes it ideal for rapid development of products and for proof of concept. This is not limited to programming novices: many industrial customers are experienced C coders but use Flowcode to get projects up and running and to manage their projects.

Here are some examples of what can be produced with Flowcode using E-blocks as a hardware platform:

I. The electronic bug uses mobile phone technology. A small patch circuit contains a microphone and amplifier that feeds into a Sony GSM module with SIM card. A PICmicro MCU Multiprogrammer, programmed with Flowcode, is used to detect an incoming call and then channel local sound to the incoming caller who can hear what is said in the room. Keypad and LCD allow various set ups with dial out at pre-determined times.

2. This medical electronics project shows an ECG sensor system. ECG data is gathered using a sensors board plugged into a PICmicro MCU Multiprogrammer. This houses a PIC16F877 programmed with Flowcode. Data is fed directly to a PC using an RS232 board and logged using a Visual Basic program. A Keypad and LCD display provide control of the system.

3. This simple MP3 player can be created from an 18 series PICmicro programmed with Flowcode. The PICmicro device connects to an SD card reader, and an MP3 decoder board. A keypad and LCD provide control of the unit which stores 125 songs.



The electronic bug



ECG sensor



MP3 player



Licensing and versions

Flexible licensing

There are several versions of Flowcode 3 that you can see in the table on the right. These differ in functionality and price. The terms used are explained below.

Code limits

For the AVR version of Flowcode there are no code size limits for any version. For the Free PICmicro version the code will limit to 2KB of compiled and assembled code (18 series PICmicro limit is 4K). For the PICmicro Student version the code will limit to 4KB of compiled and assembled code (18 series PICmicro limit is 8K).

Limited components

Free and student versions do not have all components. Limited component versions all have LED, Switch, ADC, LCD, 7-segment display, Keypad, Quad 7-segment display, Burglar alarm, Buggy and Formula Flowcode. These versions cannot have more components added to them as free downloads. Other versions include all components.

Free version

This well featured version allows you to verify that Flowcode will provide the functions you need and is also suitable for use with hardware devices like the Formula Flowcode robot and ECIO. This is a fully working version of Flowcode that has some limitations. For Flowcode for PICmicro MCUs the demo version will produce hex code for only the following: 16F628A, 16F84A, 16F877A, 18F2220, 18F4431, Formula Flowcode, and ECIO. Free versions are limited to around 50 usable icons and also have code size limitations for PICmicro microcontrollers.

Student/ home version

The student PICmicro version is limited in the compiled code size it can produce and in the number of Flowcode components provided: communications functions are not supported. The AVR student version is limited in Flowcode components but has no code size limit.

Pro version

The Pro version includes all functions, components, full code compilation size and is licensed for commercial use. Industrial users who need more than one licence will need to purchase each licence separately.

Multiuser education

Multiuser versions are fully functional like the Pro version, but these are for educational (non-commercial) use only. Only 10 and 50 user versions are available. Those requiring between 10 and 20 users will need to purchase 2 off 10 user versions.

	Free version	Flowcode Student	Flowcode Pro	Flowcode 10 concurrent users	Flowcode 50 concurrent users	
Unlimited icons	N	Y	Y	Y	Y	
Code size limit*	2K	4K	Ν	N	Ν	
All devices	Ν	Y	Y	Y	Y	
All components	Ν	N	Y	Y	Y	
Licence for commercial use	Ν	N	Y	N	Ν	
Multi-user licence for education	Ν	N	Ν	Y	Y	
Retail price**	£0	£39	£99	£350	£699	

*Code size limit only applies to PICmicro versions. Other versions use limited icon numbers to limit functionality.

**These target prices are exclusive of tax and any applicable postage charges, and may vary slightly from one region to another.

Upgrading licences

Upgrades from one type of licence (e.g. Student to Pro) to another are simply the price difference.

Versions 2 to Version 3 upgrade

Upgrades from version 2 to version 3 will be charged at 50% of the version 3 price.

Crossgrade

Customers who have a version of Flowcode for one microcrontroller will be charged at 50% of the price of Flowcode for each subsequent microcrontroller family.

Upgrade procedure

Please contact Matrix Multimedia or one of our dealers with your old serial number which is found on the inside of your CD ROM case.

Buying online

The only downloadable version available is the free version. Copies of Flowcode for purchase are only available in CD ROM form from Matrix or an authorised dealer.

Activation

Each product will need activation with a code issued by Matrix. An internet connection is recommended for this.

Details correct at time of going to press. Matrix Multimedia reserves the right to change specific





New features in version 3

The step from Flowcode 2 to Flowcode 3 is large with the software being improved in many areas. The improvements have been made with several themes in mind as you can see here:

Graphical User Interface improvements

Flowcode 3 has a number of enhancements over version 2 which makes it easier to design your program

- Making the most of your monitor real estate:
 - Zoom: Multiple zoom levels, zoom to fit
 - Tiling: horizontal tile, vertical tile
 - Smaller microcontroller on-screen device
- Helping you produce easier to read flow charts:
 - Screen icons: new graphics, description now inside icons, better comments, more icons per screen viewable
 - Screen appearance: user selected icon shading, and background colour
 - Hardware and software macros now have separate icon graphics now known as: 'macro' and 'hardware macro'
- Helping you produce better documents and output:
 - New features for printing include Print Preview, and print to screen zoom setting
 - Flowcharts can be exported to JPEG or BMP for incorporation into documents
 - Tile horizontal and Vertical and auto arrange for multiple macro viewing

Improvements to help learners

Flowcode has new features that help users to learn programming and help them migrate to the C language when ready

- Features to help users learn C
 - All icons have bubble help to display icon function
 - Icons can also produce equivalent C code of each icon as bubbles
 - Students can view the C code equivalent of the whole program
 - Students can view the Assembly code equivalent of the whole program
- Screen layout and save:
 - Screen layout is preserved on save to allow educators to build more relevant examples
- Tutorial files
 - Descriptions now included
 - Makes use of features such as labelled components to add context

Multilingual support

- Main program and help file: Dutch, English, French, German, Greek, Spanish, Portuguese
- Main program but not help file: Chinese, Danish, Finnish, Hungarian, Italian, Japanese, Korean, Romanian, Slovenian, Slovak, Thai, Turkish, Vietnamese

Software functionality improvements

New features in Flowcode 3 make it easier to create your programs and allows you to take advantage of more powerful, larger microcontrollers.

- Debugging
 - A better range of simulation speeds allows you to see your program working before downloading it to the PICmicro microcontroller
 - Alter variables whilst simulation is paused
- Type and variables:

•

- Support for I 6 bit numbers and arithmetic, choice of types includes CHAR, INT and STRING
- Support for hexadecimal and binary numbers in all dialogue boxes
- Full support for strings including string manipulation commands like ADD, LEFT, RIGHT
- Improvements to icons and their functionality:
 - New string process icon supports string manipulation
 - Interrupt icon supports a larger range of interrupts as well as custom interrupt definition. Each interrupts run a macro of your choice.
 - Improved Delay icon with a much greater range of delays
 - While icon can operate for a defined number of times
 - New string process icon supports string manipulation
- Subroutines can now have parameters passed to them, and returned
- Larger range of supported devices now includes 18 series PICmicro microcontrollers and other microcontroller families
- Undo and Redo commands
- Improved C compiler

Component improvements

New components have been introduced to allow you to incorporate a greater range of devices into your electronic system

- LCD: greater range of LCD types supported including 40 character - 2 line, 20 character, 4 line etc.
- Full LCD functions now supported with scroll and other features.
- Switches: can now be labelled, options for display vertical and horizontal, left to right or right to left.
- LEDs: can now be labelled, options for display vertical and horizontal, left to right or right to left.
- New PWM (Pulse Width modulation) component for motor control.
- Analogue component s available now include thermometer, dial, or slider
- Target communications components now include RS232, I²C, Internet web server, Internet TCP/IP, Bluetooth, CAN bus and LIN bus

Cross platform development

Programs written for the one microcontrollercan be exported and imported into Flowcode for other microcontrollers, and vice-versa. This means that programs written for one microcontroller can be used in another.



Technical specification

Flow chart icons

Input, Output, Delay, If, Connection point, Goto connection point, While, Macro, Component macro, Calculation, String calculation, Interrupt, C/ASM icon, Comment.

Virtual systems

Buggy, Burglar alarm, Formula Flowcode

Standard components

LED, Switch, Sensor, LCD, 7-segment display, Keypad, Quad 7-segment display.

Advanced components

Advanced components include: SPI bus, I²C bus, Internet, Webserver, CAN bus, LIN bus, EEPROM, IrDA, Bluetooth, PWM, AddDefines and RS232. Other components may be added to this list.

Technical requirements

Windows XP, Vista.

Output

Produces C code, ASM code and hex code compatible with the target microcontroller.

Language support (as of March 2008)

Full translations (inc. help file): Dutch, English, French, German, Greek, Spanish, Portuguese

Full translations (no help file):

Chinese, Danish, Finnish, Hungarian, Italian, Japanese, Korean, Romanian, Slovenian, Slovak, Thai, Turkish, Vietnamese

Partial translations (still waiting for updates):

Finnish

Target microcontrollers - PICmicro

12F609, 12F615, 12F629, 12F635, 12F675, 12F683

16F610, 16F616, 16F627, 16F627A, 16F628, 16F628A, 16F630, 16F631, 16F636, 16F639, 16F648A, 16F676, 16F677, 16F684, 16F685, 16F687, 16F688, 16F689, 16F690, 16F716, 16F72, 16F73, 16F737, 16F74, 16F747, 16F76, 16F767, 16F77, 16F777, 16F785, 16F818, 16F819, 16F83, 16F84, 16F84A, 16F877, 16F870, 16F877, 16F873, 16F873, 16F873, 16F874, 16F874A, 16F876A, 16F877, 16F877A, 16F88, 16F883, 16F884, 16F886, 16F887, 16F913, 16F914, 16F916, 16F917, 16F946

18F1220, 18F1230, 18F1320, 18F1330, 18F2220, 18F2221, 18F2320, 18F2321, 18F2331, 18F2410, 18F242, 18F2420, 18F2423, 18F2431, 18F2439, 18F2450, 18F2455, 18F248, 18F2480, 18F2410, 18F2510, 18F2515, 18F252, 18F2520, 18F2523, 18F2525, 18F2539, 18F2580, 18F2580, 18F2585, 18F2520, 18F2610, 18F2620, 18F2680, 18F2682, 18F2685, 18F4220, 18F4221, 18F4320, 18F4321, 18F4331, 18F4410, 18F442, 18F4420, 18F4423, 18F4431, 18F4439, 18F4450, 18F4455, 18F448, 18F4480, 18F4410, 18F4510, 18F4515, 18F452, 18F4520, 18F4523, 18F4525, 18F4539, 18F4550, 18F458, 18F4580, 18F4585, 18F4510, 18F4523, 18F4525, 18F4539, 18F4550, 18F4682, 18F4685, 18F6310, 18F6390, 18F6410, 18F6420, 18F6527, 18F6622, 18F6627, 18F6722, 18F8310, 18F8390, 18F8410, 18F8490, 18F8527, 18F8622, 18F6627, 18F8722, ECIO-28, ECIO-40, Formula Flowcode

Target microcontrollers - AVR

AT90S2313, AT90S2323, AT90S4433, AT90S8515, AT90S8535, ATtiny13, ATtiny2313, ATtiny24, ATtiny25, ATtiny26, ATtiny261, ATtiny44, ATtiny45, ATtiny461, ATtiny84, ATtiny85, ATtiny861

ATmega16, ATmega162, ATmega164P, ATmega168, ATmega32, ATmega324P, ATmega328P, ATmega48, ATmega644, ATmega8, ATmega8515, ATmega8535, ATmega88

Target microcontrollers - ARM

AT91SAM7S512, AT91SAM7S256, AT91SAM7S128, AT91SAM7S64, AT91SAM7S321, AT91SAM7S32, AT91SAM7S16, AT91SAM7S161, AT91SAM7SE32, AT91SAM7SE256, AT91SAM7SE512

Note that microcontroller compatibility changes on a frequent basis. If you have specific microcontroller requirements then please contact your dealer.

Order codes

Flowcode for PICmicro MCUs Student version: Pro version: 10 user education version: Site licence education version:	TEFLCST3 TEFLCSI3 TEFLCI03 TEFLCSL3
Flowcode for AVR MCUs Student version: Pro version: 10 user education version: Site licence education version:	TEVRST3 TEVRSI3 TEVR103 TEVRSL3
Flowcode for ARM Student version: Pro version: 10 user education version: Site licence education version:	TERMST3 TERMSI3 TERM103 TERMSL3

 Pro version:
 TEULSI3

 10 user education version:
 TEULI03

 Site licence education version:
 TEULSL3



Microtip Inc. America and AVR are trademarks of Articona of the Atmel corporation. Downloaded from <u>Elcodis.com</u> electronic components distributor