



3.6V LITHIUM CYLINDRICAL CELLS



PART NO.	X-REFERENCE	PIC #	VOLTS	CAP. mAh	DIMENSIONS (mm)		CELL SIZE	TERMINATION*
					DIAMETER	HEIGHT		
COMP-4-SAFT	LS3BA,LS14250BA	1	3.6	1000	14.5	25.2	1/2AA	—
COMP-4-1-SAFT	LS14250 ST	1	3.6	1000	14.5	25.2	1/2AA	1
COMP-4-3R SAFT	LS14250 3PF	1	3.6	1000	14.5	25.2	1/2AA	3
COMP-4-5 SAFT	LS14250 AX	1	3.6	1000	14.5	25.2	1/2AA	5
COMP-4-MAX-S	ER3STC	2	3.6	750	14.5	25.4	1/2AA	—
COMP-4-1-MAX-S	ER3STT	2	3.6	750	14.5	25.4	1/2AA	1
COMP-4-MAX	ER3#5TC	3	3.6	750	14.5	30.5	1/2AA	—
COMP-4-1-MAX	ER3TT	3	3.6	750	14.5	30.5	1/2AA	1
COMP-4-5-MAX	ER3#4AX	3	3.6	750	14.5	30.5	1/2AA	5
COMP-200	TL-4902/S	4	3.6	1200	14.5	25.2	1/2AA	—
COMP-200-1	TL-4902/T	4	3.6	1200	14.5	25.2	1/2AA	1
COMP-200-3	TL-4902/PT	4	3.6	1200	14.5	25.2	1/2AA	3
COMP-200-3R	TL-4902/TP	4	3.6	1200	14.5	25.2	1/2AA	3
COMP-200-5	TL-4902/P	4	3.6	1200	14.5	25.2	1/2AA	5
COMP-4	TL-5101/S	4	3.6	950	14.5	25.2	1/2AA	—
COMP-4-1	TL-5101/T	4	3.6	950	14.5	25.2	1/2AA	1
COMP-4-2	TL-5101/PT2	4	3.6	950	14.5	25.2	1/2AA	2
COMP-4-3	TL-5101/PT	4	3.6	950	14.5	25.2	1/2AA	3
COMP-4-3R	TL-5101/TP	4	3.6	950	14.5	25.2	1/2AA	3
COMP-4-5	TL-5101/P	4	3.6	950	14.5	25.2	1/2AA	5
COMP-95	TL-5151/S	4	3.6	700	14.5	25.2	1/2AA	—
COMP-95-1	TL-5151/T	4	3.6	700	14.5	25.2	1/2AA	1
COMP-95-5	TL-5151/P	4	3.6	700	14.5	25.2	1/2AA	5
LITH-6	TL-2150/S	4	3.6	950	14.5	25.2	1/2AA	—
LITH-6-1	TL-2150/T	4	3.6	950	14.5	25.2	1/2AA	1
LITH-6-3	TL-2150/PT	4	3.6	950	14.5	25.2	1/2AA	3
LITH-6-3R	TL-2150/TP	4	3.6	950	14.5	25.2	1/2AA	3
LITH-6-5	TL-2150/P	4	3.6	950	14.5	25.2	1/2AA	5
LITH-7	TL-5111/S(VENTED)	4	3.6	850	14.5	25.2	1/2AA	—
LITH-21	TL-5902/S	4	3.6	1200	14.5	25.2	1/2AA	—
LITH-21-1	TL-5902/T	4	3.6	1200	14.5	25.2	1/2AA	1
LITH-21-5	TL-5902/P	4	3.6	1200	14.5	25.2	1/2AA	5
COMP-29-MAX	ER17/33#5TC	5	3.6	1500	17.0	36.0	2/3A	—
COMP-29-1-MAX	ER17/33TT	5	3.6	1500	17.0	36.0	2/3A	1
COMP-29-2-MAX	ER17/33#2PC	5	3.6	1500	17.0	36.0	2/3A	2
COMP-29-5-MAX	ER17/33#4AX	5	3.6	1500	17.0	36.0	2/3A	5
COMP-6-SAFT	LS6BA, LS14500BA	6	3.6	2250	14.5	50.5	AA	—
COMP-6-1 SAFT	LS14500 ST	6	3.6	2250	14.5	50.5	AA	1
COMP-6-5 SAFT	LS14500 AX	6	3.6	2250	14.5	50.5	AA	5
COMP-6HC SAFT	LS14500 C	6	3.6	2750	14.5	50.5	AA	—
COMP-6-MAX	ER6#5TC	7	3.6	1900	14.5	50.5	AA	—
COMP-6-1 MAX	ER6CTT	7	3.6	1900	14.5	50.5	AA	1
COMP-6-2 MAX	ER6C#2PC	7	3.6	1900	14.5	50.5	AA	2
COMP-6-5-MAX	ER6#4AX	7	3.6	1900	14.5	50.5	AA	5
COMP-6	TL-5104/S	8	3.6	2100	14.5	50.5	AA	—
COMP-6-1	TL-5104/T	8	3.6	2100	14.5	50.5	AA	1
COMP-6-2	TL-5104/PT2	8	3.6	2100	14.5	50.5	AA	2

*For terminations see page 48 & 49.

3.6V LITHIUM CYLINDRICAL CELLS



PART NO.	X-REFERENCE	PIC #	VOLTS	CAP. mAh	DIMENSIONS (mm)		CELL SIZE	TERMINATION*
					DIAMETER	HEIGHT		
COMP-6-5	TL-5104/P	8	3.6	2100	14.5	50.5	AA	5
COMP-65	TL-5903/S	8	3.6	2400	14.5	50.5	AA	—
COMP-65-1	TL-5903/T	8	3.6	2400	14.5	50.5	AA	1
COMP-65-5	TL-5903/P	8	3.6	2400	14.5	50.5	AA	5
LITH-10	TL-2100/S	8	3.6	2100	14.5	50.5	AA	—
LITH-10-1	TL-2100/T	8	3.6	2100	14.5	50.5	AA	1
LITH-10-5	TL-2100/P	8	3.6	2100	14.5	50.5	AA	5
LITH-11	TL-5114/S(VENTED)	8	3.6	1900	14.5	50.5	AA	—
LITH-14	TL-2200/S	9	3.6	7200	26.2	50.0	C	—
LITH-14-1	TL-2200/T	9	3.6	7200	26.2	50.0	C	1
LITH-14-2	TL-2200/TP	9	3.6	7200	26.2	50.0	C	2
LITH-14-5	TL-2200/P	9	3.6	7200	26.2	50.0	C	5
LITH-14HC	TL-5920/S	9	3.6	8500	26.2	50.0	C	—
LITH-14-SAFT	LSH14BA	10	3.6	5200	26.1	50.0	C	—
LITH-14-1 SAFT	LSH14T	10	3.6	5200	26.1	50.0	C	1
LITH-15	TL-2300/S	12	3.6	16500	32.9	61.5	D	—
LITH-15-1	TL-2300/T	12	3.6	16500	32.9	61.5	D	1
LITH-15HC	TL-5930/S	11	3.6	19000	33.6	61.5	D	—
LITH-15-SAFT	LSH20BA	11	3.6	13000	33.6	61.5	D	—
LITH-15-1 SAFT	LSH20T	11	3.6	13000	33.6	61.5	D	1
LITH-16	TL-5137/S	13	3.6	35000	32.9	124.5	DD	—
LITH-16-1	TL-5137/T	13	3.6	35000	32.9	124.5	DD	1
COMP-29-T3-MAX	ER17/33T3	14	3.6	1500	17.0	34.0	2/3A	3
COMP-64	ER10/28#4AX	15	3.6	410	10.0	28.0	N	5
COMP-84	ER10/28/CONN	16	3.6	410	10.0	28.0	N	CONN
COMP-6-WK19	ER6WK9	17	3.6	1900	14.5	50.5	AA	CONN
COMP-88	LTC-7PN	18	3.5	750	25.0 X 15.0 X 5.0	—	—	4 PIN
COMP-88A	LTC-7P	19	3.5	750	30.0 X 17.0 X 7.0	—	—	4 PIN
COMP-100	TL5155/S	20	3.6	1450	14.5	33.5	2/3AA	—
COMP-100-1	TL5155/T	20	3.6	1450	14.5	33.5	2/3AA	1
COMP-100-2	TL5155/PT2	20	3.6	1450	14.5	33.5	2/3AA	2
COMP-100-3	TL5155/PT	20	3.6	1450	14.5	33.5	2/3AA	3
COMP-100-5	TL5155/P	20	3.6	1450	14.5	33.5	2/3AA	5
COMP-127	B9696T	4	3.6	800	14.5	25.2	1/2AA	—
COMP-139	TL-5955/S	20	3.6	1650	14.5	33.5	2/3AA	—
COMP-201	TL-2155/S	20	3.6	1450	14.5	33.5	2/3AA	—
COMP-201-1	TL-2155/T	20	3.6	1450	14.5	33.5	2/3AA	1
COMP-201-3	TL-2155/PT	20	3.6	1450	14.5	33.5	2/3AA	3
COMP-201-3R	TL-2155/TP	20	3.6	1450	14.5	33.5	2/3AA	3
COMP-201-5	TL-2155/P	20	3.6	1450	14.5	33.5	2/3AA	5
COMP-4HC SAFT	LS14250C BA	21	3.6	1250	14.5	25.2	1/2AA	—
LITH-36	LS26500 BA	22	3.6	7300	26.1	50.0	C	—
LITH-37	LS33600BA	23	3.6	16500	33.6	61.5	D	—

*For terminations see page 48 & 49.