



THE DURACELL PROCELL DISTRIBUTION NETWORK

DURACELL PROCELL batteries and flashlights as well as DURACELL COPPERTOP®, DURACELL ULTRA and MALLORY® branded batteries are available through Duracell network of medical and industrial distributors.

THE ALKALINE ADVANTAGE

Compared to Super Heavy Duty zinc carbon batteries, DURACELL® PROCELL® alkaline batteries:

- provide superior end-user value and savings on overall battery cost.
- have both a higher energy density and a greater power capability.
- provide up to ten times the service life in high drain and/or high voltage devices.
- operate longer and have greater capacity retention when stored in temperature extremes.
- are less likely to leak, protecting important equipment.
- have a 7 year freshness guarantee.

Regional Office

Eastern Region:
The Gillette Company
Commercial Operations North America
1145 Sanctuary Parkway, Suite 425
Alpharetta, GA 30004
(770) 777-3541

For more information, visit our website at www.duracell.com/procell.

DURACELL®



PROFESSIONAL PRODUCTS

The Gillette Company
Commercial Operations North America
Prudential Tower Building, Boston, MA 02199-8004



©2004 The Gillette Company
DURP9901-04

DURACELL® PROCELL™ BATTERIES FOR PROFESSIONAL APPLICATIONS

When it comes to the workplace, we at Duracell recognize that professionals demand dependable, long lasting performance. That's why we offer DURACELL® PROCELL™ professional batteries. A full line of DURACELL PROCELL alkaline, zinc air, lithium, and specialty batteries is available and is priced and packaged exclusively for professional applications. In addition to batteries, a complete selection of professional flashlights is also available covering most business needs.



DURACELL PROCELL BATTERIES

All DURACELL PROCELL batteries are manufactured to rigorous specifications to meet the high standards of durability and longevity professional users expect. All DURACELL PROCELL products are backed by Duracell's guarantee of quality and workmanship.

WHY DO DURACELL PROCELL BATTERIES LAST SO LONG?

Duracell conducts extensive testing and analysis of battery usage patterns to determine the factors having the greatest impact on battery performance. These efforts have resulted in the development of our longest lasting battery ever.

Over the last ten years a substantial investment in battery research and development has yielded significant increases in Duracell battery performance.

Duracell is committed to the development of innovations and improvements that will deliver increased customer value and satisfaction.

DURACELL... THE COMPANY BEHIND THE DURACELL PROCELL BRAND NAME

Duracell is the world's leading manufacturer and marketer of high performance alkaline batteries. In addition, Duracell markets primary lithium batteries, zinc air batteries, rechargeable nickel metal hydride batteries, and a range of specialty batteries.

DURACELL... THE BATTERY CATEGORY EXPERTS

Duracell maintains a strong commitment to grow the battery business with each of our professional customers. Every Duracell Professional Products sales team member is a battery category expert and is solely dedicated to cater to the business needs of Duracell professional customers.

CONTENTS PAGE

DURACELL® PROCELL™ PRODUCTS

ALKALINE	3
LANTERN/MEDICAL	4
ELECTRONIC	5
FLASHLIGHTS	6-7
DURACELL PRODUCTS	
ULTRA	8
ALKALINE	9
LITHIUM	10
PHOTO	11
KEYLESS ENTRY/SECURITY	12
WATCH/ELECTRONIC	13
HOME MEDICAL	14
HEARING AID	15
CAMCORDER	16
MALLOTT PRODUCTS	
SUPER	17
CROSS REFERENCE	18-22

DURACELL® PROCELL™

ALKALINE BATTERIES

DURACELL® PROCELL™ alkaline batteries deliver outstanding performance and reliability. Major advantages are:

- long lasting and dependable – even after seven years of storage
- last up to ten times longer than super heavy duty zinc carbon batteries in power demanding applications
- long service life at high drain discharges
- operate reliably in temperature extremes of -20°C to 54°C
- date coded to ensure freshness
- economical bulk packaging for professional applications
- contain no added mercury



PC1300

SPECIFICATIONS	
Size/System:	Size D Alkaline
Voltage:	1.5
Max. Diameter:	1.346"
Max. Height:	2.421"
Average Weight:	4.86 oz (138.0g)
Maximum Volume:	3.44 in. ³ (56.4cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Flashlights, Radios, Tape Recorders

PC1400

SPECIFICATIONS	
Size/System:	Size C Alkaline
Voltage:	1.5
Max. Diameter:	1.031"
Max. Height:	1.969"
Average Weight:	2.29 oz (65.0g)
Maximum Volume:	1.64 in. ³ (26.9cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Flashlights, Radios, Tape Recorders



PC1500

SPECIFICATIONS	
Size/System:	Size AA Alkaline
Voltage:	1.5
Max. Diameter:	.571"
Max. Height:	1.988"
Average Weight:	0.83 oz (23.6g)
Maximum Volume:	0.51 in. ³ (8.4cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Pagers, Remotes, Flashlights, Calculators



PC2400

SPECIFICATIONS	
Size/System:	Size AAA Alkaline
Voltage:	1.5
Max. Diameter:	.413"
Max. Height:	1.752"
Average Weight:	0.39 oz (11.0g)
Maximum Volume:	0.23 in. ³ (3.8cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Pagers, Flashlights, TV Remotes



PC1604

SPECIFICATIONS	
Size/System:	9 Volt Alkaline
Voltage:	9.0
Max. Length:	.689"
Max. Width:	1.043"
Max. Height:	1.909"
Average Weight:	1.62 oz (45.9g)
Maximum Volume:	1.39 in. ³ (22.8cm. ³)
Terminals:	Miniature Snap
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Infusion Pumps, Wireless Microphones, Smoke Alarms, Radios

www.duracell.com/procell

DURACELL PROCELL

ALKALINE LANTERN BATTERIES

DURACELL PROCELL alkaline lantern batteries last up to twice as long as super heavy duty zinc carbon batteries and provide an extra measure of leakage resistance for critical applications. Like the popular size DURACELL PROCELL alkaline batteries, DURACELL PROCELL lantern batteries offer:

- a long shelf life
- reliable performance at temperature extremes
- date coding to ensure freshness
- bulk packaging

MEDICAL APPLICATION BATTERIES

At DURACELL we recognize that people using batteries in the workplace have special requirements. In hospitals and healthcare facilities throughout the world, DURACELL PROCELL batteries keep critical electronic equipment alive and working.

PC903



SPECIFICATIONS	
Size/System:	Alkaline
Voltage:	7.5
Max. Length:	2.250"
Max. Width:	4.062"
Max. Height:	3.749"
Average Weight:	78.37 oz (2,222.6g)
Average Volume:	106.0 in. ³ (1,737cm. ³)
Terminals:	Insulated Screw
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Lanterns

PC915



SPECIFICATIONS	
Size/System:	Alkaline
Voltage:	6.0
Max. Length:	2.685"
Max. Width:	2.685"
Max. Height:	PC915 4.409"
Average Weight:	21.60 oz (612g)
Average Volume:	PC915 29.20 in. ³ (478.5cm. ³)
Terminals:	PC915 Insulated Screw
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Lanterns

DA146



SPECIFICATIONS	
Size/System:	Zinc Air
Voltage:	8.4
Max. Length:	1.010"
Max. Width:	.648"
Max. Height:	1.75"
Rated Capacity:	1,300 mAh at 1,300Ω to 6.0V at 21°C (70°F)
Average Weight:	1.27 oz (36.0g)
Average Volume:	1.09 in. ³ (17.86cm. ³)
Terminals:	Miniature Snap
Operating Temperature Range:	32°F to 122°F (0°C to 50°C)
Primary Usage:	Telemetry Devices

PL1604



SPECIFICATIONS	
Size/System:	Lithium-Manganese Dioxide
Voltage:	9
Max. Length:	26.4mm
Max. Width:	17.1mm
Max. Height:	48.8mm
Rated Capacity:	1.2Ah at 900 Ohm to 5.4V
Average Weight:	1.2 oz (34gm)
Average Volume:	1.3 in. ³ (21.4cm. ³)
Terminals:	Miniature Snap
Operating Temperature Range:	-4°F to 140°F (-20°C to 60°C)
Primary Usage:	Bone Growth Stimulators, Wireless Alarms, Handheld Scanners

DURACELL PROCELL

ELECTRONIC BATTERIES

DURACELL PROCELL electronic batteries are designed specifically for medical and electronic equipment.

DURACELL PROCELL electronic batteries:

- provide optimum performance in applications such as glucose meters, pagers, penlights and TV remote controls
- are bulk packaged



PL123A



SPECIFICATIONS			
Size/System:	Size 123A Lithium/Manganese Dioxide	Average Weight:	0.60 oz (17.0g)
Voltage:	3.0	Terminals:	Flat, Recessed Negative Terminal
Max. Diameter:	.669"	Operating Temperature Range:	-40°F to 140°F (-40°C to 60°C)
Max. Height:	1.358"	Primary Usage:	Photo
Rated Capacity:	1,400 mAh at 1000 to 2.0V at 20°C (68°F)		

PC9100



SPECIFICATIONS			
Size/System:	Size N Alkaline	Maximum Volume:	0.21 in. ³ (3.4cm. ³)
Voltage:	1.5	Terminals:	Flat
Max. Diameter:	.472"	Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Max. Height:	1.189"	Primary Usage:	Hearing Aids, Glucose Meters, Flashlights
Rated Capacity:	800 mAh at 1000 to 0.8V at 21°C (70°F)		
Average Weight:	0.34 oz (9.6g)		

PC7K67



SPECIFICATIONS			
Size/System:	Size J Alkaline	Average Weight:	1.20 oz (34.0g)
Voltage:	6.0	Maximum Volume:	0.96 in. ³ (15.7cm. ³)
Max. Length:	.362"	Terminals:	Recessed Flat
Max. Width:	1.402"	Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Max. Height:	1.909"	Primary Usage:	Glucose Meters, TV Remotes
Rated Capacity:	580 mAh at 3400 to 3.2V at 21°C (70°F)		

www.duracell.com/procell

DURACELL PROCELL

PROFESSIONAL FLASHLIGHTS

DURABLE. RELIABLE. OUR BEST FLASHLIGHTS EVER!

Duracell® Procell® flashlights are a comprehensive line of products designed for a wide range of key professional applications – our flashlight line has been built to shine in even the toughest environments.

PCIND

Heavy Duty Industrial Light

- Oil and chemical resistant Polypropylene body/head/endcap
- Reliable slide switch with protective switch guard prevents accidental ON and is oil/chemical resistant
- Computerized parabolic reflector provides high light transmittance
- Large hanger hook
- Spare bulb holder



PCECON-W / PCECON-B / PCECON-BM

Economy Lights

- Oil and chemical resistant Polypropylene body/head
- Computerized parabolic reflector delivers high light transmittance
- "No-Roll" hexagon head shape
- Light weight
- PCECON-BM comes with a 20 lb. magnet
- Bright Krypton bulb



PCMSHA

Explosion Proof Safety Light

- Oil, grease and chemical resistant high density Polypropylene light
- Bright orange color
- US Department of Labor MSHA certified and UL approved
- Switch guard protects against accidental ON
- Bright Krypton bulb
- Spare bulb holder



PCPEN

Aluminum Pen Light

- Slim, lightweight aluminum tube body
- Powered by AAA batteries
- Sturdy pocket clip
- High quality pre-focused bulb



PCEXPD / PCVOYA

Heavy Duty Rubber Lights

- Heavy-duty construction
- Shock absorbent and water resistant
- Soft rubber body in ergonomic design
- Bright Krypton bulb
- Handy lanyard with quick break-off release adjustable knob



PCL4D

Lantern Light

- Heavy-duty body with blow molded construction
- Floatable
- Bright Krypton bulb
- Battery adapter - holds either 4 "D" cells or one 6V lantern battery
- Specular parabolic reflector and recessed lens for added lens protection



DURACELL® ALKALINE BATTERIES ULTRA

MX1300



SPECIFICATIONS	
Size/System:	D Alkaline
Voltage:	1.5
Max. Diameter:	1.346"
Max. Height:	2.421"
Primary Usage:	High Intensity Flashlights, Portable Color TVs, Portable Stereos

MX1400



SPECIFICATIONS	
Size/System:	C Alkaline
Voltage:	1.5
Max. Diameter:	1.031"
Max. Height:	1.969"
Primary Usage:	Portable Stereos, High Performance Toys, High Intensity Flashlights

MX1500



SPECIFICATIONS	
Size/System:	AA Alkaline
Voltage:	1.5
Max. Diameter:	.571"
Max. Height:	1.988"
Primary Usage:	Flash Cameras, Digital Cameras, CD Players

MX1604



SPECIFICATIONS	
Size/System:	9V Alkaline
Voltage:	9.0
Max. Length:	.689"
Max. Width:	1.043"
Max. Height:	1.909"
Primary Usage:	Smoke Alarms, Toys, Wireless Transmission Devices

MX2400



SPECIFICATIONS	
Size/System:	AAA Alkaline
Voltage:	1.5
Max. Diameter:	.413"
Max. Height:	1.752"
Primary Usage:	Flash Cameras, Wireless Communication and Transmission Devices



DURACELL® ULTRA

is specifically formulated for today's photo/electronic devices. Duracell Ultra continues to be designed to meet the ever increasing power demands of a new generation of devices.

DURACELL® ALKALINE BATTERIES

MN1300



SPECIFICATIONS	
Size/System:	D Alkaline
Voltage:	1.5
Max. Diameter:	1.346"
Max. Height:	2.421"
Primary Usage:	Flashlights, Radios, Recorders, Toys

MN1400



SPECIFICATIONS	
Size/System:	C Alkaline
Voltage:	1.5
Max. Diameter:	1.031"
Max. Height:	1.969"
Primary Usage:	Flashlights, Radios, Recorders, Toys

MN1500



SPECIFICATIONS	
Size/System:	AA Alkaline
Voltage:	1.5
Max. Diameter:	.571"
Max. Height:	1.988"
Primary Usage:	Flashlights, Radios, Recorders, Toys, Calculators, Pagers, CD Players, Electronic Games

MN1604



SPECIFICATIONS	
Size/System:	9V Alkaline
Voltage:	9.0
Max. Length:	.689"
Max. Width:	1.043"
Max. Height:	1.909"
Primary Usage:	Radios, Toys, Calculators, Smoke Alarms

MN2400



SPECIFICATIONS	
Size/System:	AAA Alkaline
Voltage:	1.5
Max. Diameter:	.413"
Max. Height:	1.752"
Primary Usage:	Flashlights, Calculators, Pagers, Remote Controls



DURACELL® COPPERTOP®

is engineered for devices consumers use most. DURACELL COPPERTOP is specifically designed for everyday devices and provides the highest quality and dependability.

DURACELL®

LITHIUM BATTERIES

Duracell's lithium/manganese dioxide batteries represent one of the latest advances in primary battery technology. For applications with a high current pulse (e.g., photoflash) and continuous drain, Duracell offers high rate 3 and 6-volt lithium batteries. Low power lithium coin cells are also available for use in memory backup applications and small electronic devices. All DURACELL® lithium batteries provide:

- very high energy density and excellent rate capability
- up to 4 times the power of alkaline batteries
- wide operating temperature range (-40°F to 140°F) and excellent low temperature performance
- excellent shelf life (0.5 percent capacity loss per year at room temperature)

CR2



SPECIFICATIONS	
System:	Lithium
Voltage:	3.0
Max. Diameter:	.614"
Max. Height:	1.063"
Primary Usage:	Photo

123



SPECIFICATIONS	
System:	Lithium
Voltage:	3.0
Max. Diameter:	.669"
Max. Height:	1.358"
Primary Usage:	Photo

DL1/3N



SPECIFICATIONS	
System:	Lithium
Voltage:	3.0
Max. Diameter:	.457"
Max. Height:	.425"
Primary Usage:	Photo

223



SPECIFICATIONS	
System:	Lithium
Voltage:	6.0
Max. Length:	.768"
Max. Width:	1.378"
Max. Height:	1.417"
Primary Usage:	Photo

CRV3



SPECIFICATIONS	
System:	Lithium
Voltage:	3.0
Max. Diameter:	.575"
Max. Width:	1.126"
Max. Height:	2.055"
Primary Usage:	Photo

245



SPECIFICATIONS	
System:	Lithium
Voltage:	6.0
Max. Length:	.669"
Max. Width:	1.339"
Max. Height:	1.772"
Primary Usage:	Photo

DURACELL®

PHOTO BATTERIES



Photo Card Size: 3.5" L x 3.5" W



DL1/3N



SPECIFICATIONS	
System:	Lithium
Voltage:	3.0
UPC:	000 41 333 11310 4
Primary Usage:	Photo

MNI75



SPECIFICATIONS	
System:	Alkaline
Voltage:	7.5
UPC:	000 41 333 11706 5
Primary Usage:	Invisible Fence Per Collars, Power Microphones, Instruments

MS76



SPECIFICATIONS	
System:	Silver Oxide
Voltage:	1.5
UPC:	000 41 333 17605 5
Primary Usage:	Photo, Calculators, Home Security Devices

MX2500



SPECIFICATIONS	
Size/System:	AAAA Alkaline
Voltage:	1.5
UPC:	000 41 333 22207 3
Primary Usage:	Laser Pointer, Penlight, Voice Recorder

PX28L



SPECIFICATIONS	
System:	Lithium
Voltage:	6.0
UPC:	000 41 333 12810 8
Primary Usage:	Photo, Glucometers

PX625A



SPECIFICATIONS	
System:	Alkaline
Voltage:	1.5
UPC:	000 41 333 16505 9
Primary Usage:	Photo, Glucometers

DURACELL®

KEYLESS ENTRY/SECURITY BATTERIES



DL1616

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 11609 9
Card Size: 3.5" L x 1.75" W
Primary Usage: Organizers



DL1620

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 16210 2
Card Size: 3.5" L x 1.75" W
Primary Usage: Computer Memory, Security Devices



DL2016

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 10110 1
Card Size: 3.5" L x 1.75" W
Primary Usage: Keyless Entry Systems, Calculators



DL2025

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 10210 8
Card Size: 3.5" L x 1.75" W
Primary Usage: Organizers, Photographic Memory Backup



DL2430

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 14310 1
Card Size: 3.5" L x 3.5" W
Primary Usage: Pet Flea Collars, Photo Memory



DL2450

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 14510 5
Card Size: 3.5" L x 3.5" W
Primary Usage: Glucometers, Photo Memory, Keyless Entry Systems



MN21

SPECIFICATIONS
System: Alkaline
Voltage: 1.2
UPC: (1-pack) 000 41333 12106 2
(2-pack) 000 41333 00406 8
Card Size: (1-pack) 3.5" L x 3.5" W
(2-pack) 3.5" L x 1.75" W
Primary Usage: Car Alarms, Home Security Devices, Garage Door Openers



MN27

SPECIFICATIONS
System: Alkaline
Voltage: 1.2
UPC: 000 41333 52387 3
Card Size: 3.5" L x 3.5" W
Primary Usage: Mercedes, Lexus and Toyota Keyless Entry Remotes



DURACELL®

WATCH/ELECTRONIC BATTERIES



Watch Card Size:
3.5" L x 1.75" W



D301/386

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 11009 7

D303/357

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 13009 5

D309/393

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 19009 8

D319

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 10809 4

D361/362

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 12609 8

D364

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 16409 0

D370/371

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 10709 7

D376

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 10909 1

D377

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 17709 0

D379

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 13709 4

D381/391

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 11809 3

D384/392

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 14809 0

D389/390

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 19809 5

D395/399

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 15909 6

D396/397

SPECIFICATIONS
System: Silver Oxide
Voltage: 1.5
UPC: 000 41333 16909 5



DL1025


SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 10710 3



DL1216

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: 000 41333 10810 0

DURACELL® HOME MEDICAL BATTERIES



DL2032

SPECIFICATIONS
System: Lithium
Voltage: 3.0
UPC: (1-pack) 000 41333 10310 5
(2-pack) 000 41333 54210 2
Card Size: (1-pack) 3.5" L x 1.75" W
(2-pack) 3.5" L x 3.5" W
Primary Usage: Car Security,
Organizers, Glucometers



MN9100

SPECIFICATIONS
Size/System: N Alkaline
Voltage: 1.5
UPC: 000 41333 29101 7
Card Size: 3.5" L x 3.5" W
Primary Usage: Photo, Pagers,
Calculators, Medical Equipment



PX28A

SPECIFICATIONS
System: Alkaline
Voltage: 6.0
UPC: 000 41333 22805 1
Card Size: 3.5" L x 3.5" W
Primary Usage: Photo,
Medical Equipment, Glucometers



PX76A675

SPECIFICATIONS
System: Alkaline
Voltage: 1.5
UPC: 000 41333 17505 8
Card Size: 3.5" L x 3.5" W
Primary Usage: Photo,
Calculators



7K67

SPECIFICATIONS
System: J Alkaline FLAT-PAK®
Voltage: 6.0
UPC: 000 41333 17705 2
Card Size: 3.5" L x 3.5" W
Primary Usage: Photo, TV Remotes,
Medical Equipment

DURACELL® HEARING AID BATTERIES



Product Code	Nominal Voltage/ Chemistry	Dimensions in Inches Max. Diameter Max. Height	Capacity (mAh)
DA10	1.4 Zinc Air	.228" .142"	90
DA13	1.4 Zinc Air	.311" .213"	275

Product Code	Nominal Voltage/ Chemistry	Dimensions in Inches Max. Diameter Max. Height	Capacity (mAh)
DA312	1.4 Zinc Air	.311" .142"	150
DA675	1.4 Zinc Air	.457" .213"	600

DURACELL® CAMCORDER BATTERIES



Product Code	Primary Usage	Chemistry	Nominal Voltage	Max. Length	Max. Width	Max. Height	Capacity (mAh)
DR5	Nikon, Panasonic, RCA and Sony Camcorders	Lithium Ion	7.2	0.9"	1.5"	2.78"	1,600
DR7	Sharp Camcorders	Nickel Metal Hydride	3.6	.76"	2.21"	2.12"	2,500
DR8	Hitachi, RCA and Minolta Camcorders	Nickel Metal Hydride	6.0	.76"	1.82"	3.52"	1,800
DR10	GE, JVC, Magnavox, Minolta, Nikon, Panasonic, RCA, Sanyo, Sharp and Sony Camcorders	Nickel Metal Hydride	6.0	.76"	1.82"	3.52"	2,200
DR11	GE, JVC, Magnavox, Minolta, Nikon, Panasonic, RCA, Sanyo, Sharp and Sony Camcorders	Nickel Metal Hydride	6.0	1.44"	1.82"	3.52"	4,300
DR12	Canon Camcorders	Nickel Metal Hydride	6.0	1.46"	1.85"	3.58"	4,300

MALLORY® SUPER BATTERIES

Environmentally improved MALLORY® Super batteries:

- are free of any added mercury
- require no special method of disposal
- are economically priced and bulk packaged
- are appropriate for low drain, intermittent and infrequent usage applications

M135SHD



SPECIFICATIONS

Size/System:	D Heavy Duty Zinc Carbon	Average Weight:	3.27 oz (92.8g)
Voltage:	1.5	Average Volume:	3.17 in. ³ (51.96cm. ³)
Max. Diameter:	1.346"	Terminals:	Flat
Max. Height:	2.421"	Primary Usage:	Flashlights

M145SHD



SPECIFICATIONS

Size/System:	C Heavy Duty Zinc Carbon	Average Weight:	1.81 oz (51.4g)
Voltage:	1.5	Average Volume:	1.52 in. ³ (24.91cm. ³)
Max. Diameter:	1.031"	Terminals:	Flat
Max. Height:	1.969"	Primary Usage:	Flashlights

M155SHD



SPECIFICATIONS

Size/System:	AA Heavy Duty Zinc Carbon	Average Weight:	.65 oz (18.3g)
Voltage:	1.5	Average Volume:	.44 in. ³ (7.2cm. ³)
Max. Diameter:	.571"	Terminals:	Flat
Max. Height:	1.988"	Primary Usage:	Flashlights

M9VSHD



SPECIFICATIONS

Size/System:	9V Heavy Duty Zinc Carbon	Average Weight:	1.36 oz (38.5g)
Voltage:	9.0	Average Volume:	1.25 in. ³ (20.5cm. ³)
Max. Length:	.689"	Terminals:	Miniature Snap
Max. Width:	1.043"	Primary Usage:	Smoke Alarms
Max. Height:	1.909"		

DURACELL

Comprehensive Battery Cross Reference

PROCELL

DURACELL PROCELL ALKALINE BATTERIES

DURACELL/PROCELL	Voltage	Type	NEDA Industrial/Consumer	Eveready Industrial/Consumer	Rayovac Industrial/Consumer	Bright Star Consumer	Panasonic Industrial
PC1300	1.5	D	13AC13A	EN95/E95	AL-D/813	7520	AM1
PC1400	1.5	C	14AC14A	EN93/E93	AL-C/814	7522	AM2
PC1500	1.5	AA	15AC15A	EN91/E91	AL-AA/815	7524	AM3
PC1604	9.0	9 VOLT	1604AC1604A	EN22/E22	AL-9V/A1604	7590	6AM6
PC2400	1.5	AAA	24AC24A	EN92/E92	AL-AAA/824	7526	AM4

DURACELL PROCELL ALKALINE LANTERN BATTERIES

PROCELL	Voltage	Type	NEDA Industrial/Consumer	Eveready Industrial/Consumer	Koehler-Bright Star
PC983	7.5	Screw Terminal Lantern	903AC/—	EN715/—	—
PC915	6.0	Screw Terminal Lantern	915AC/915A	—	—

DURACELL PROCELL ELECTRONIC BATTERIES

PROCELL	Voltage	Eveready	Panasonic	Kodak	Varta	Sanyo	Rayovac	Maxell	NEDA	IEC	Other
PL123A	3.0	EL123AP	CR123A	K123LA	CR123A	CR123A	RL123A	CR123	5018LC	CR17345	—
PC7867	6.0	S39	4LR-61	KJ	4018	—	RJ-1	—	1412AP	4LR61	Size J
PC9100	1.5	E90	AMS	KN	4001	—	RN-2	—	910A	LR1	Size N

DURACELL PROCELL MEDICAL APPLICATION BATTERIES

PROCELL	Voltage	Type	Eveready	NEDA	Ultralife
DA146	8.4	Zinc Air	AC146X	7004Z	—
PL1604	9.0	Lithium	L522	1604LC	U9VL

DURACELL PROCELL PROFESSIONAL FLASHLIGHTS

PROCELL	Voltage	Type	Eveready	Rayovac	Koehler-Bright Star	Panasonic
PECEON-W	3.0	Economy, Lightweight Design, Bright Krypton Bulb	3251WH	—	—	—
PCL4D	6.0	Industrial Lantern, Heavy Duty Construction w/Battery Adapter	2081ND	L295-S	2001	—
PCVOYA	3.0	Heavy Duty Rubber Construction, Weather Resistant	R215ND	—	—	—
PECEPD	3.0	Heavy Duty Rubber Construction, Weather Resistant	4250ND	—	RBR219	RBD210
PECEON-B	3.0	Economy, Lightweight Design, Bright Krypton Bulb	3251R	IN2	2618	2618
PECEON-BM	3.0	Economy, Lightweight Design, 20h. Magnet, Bright Krypton Bulb	1251	IN2-ML	1618-ML	1618
PCMSHA	3.0	UL and MSHA Approved, Safety High Density Polypropylene, Spare Bulb Holder	1259	IN2-MS	2117	—
PCPEN	3.0	Stim. Aluminum Design Penlight w/Pocket Clip and Profocused Bulb	6212WH	V2AAA-B	100	—
PCIND	3.0	Heavy Duty Polypropylene, Hanger Ring and Switch Guard, Spare Bulb Holder	E250Y	IN2-K	K-2618	—

DURACELL OTHER PHOTO/ELECTRONIC BATTERIES

DURACELL	Voltage	Type	Eveready	Panasonic	Kodak	Varta	Rayovac	Maxell	Toshiba	AWI	NEDA	IEC	Other
MN175	7.5	Alkaline	—	—	—	—	—	—	—	—	1501M	SNR44	EP175, HM-5C, PC175A, TR175
MX2500	1.5	Alkaline	E96	—	—	—	—	—	—	—	—	—	—
MN9100	1.5	Alkaline	E90	AMS	KN	4001	810	—	CR1	—	910A	CR1	Size N
MS76	1.5	Silver	EPX76	G-13	KS76	V76PX	RS76	SR44P	SR44	S15	1107SOP	SR44	B-SR44, 76, 4075, SP76
PX28A	6.0	Alkaline	A544	4LR44	K28A	V34PX	—	4LR44P	4LR44	—	1414A	4LR44	—
PX625A	1.5	Alkaline	EPX625	H-D	KX625	V625PX	RPX625	—	MR9	MO1	1124MP	MR9	M20, PX13, 8300, PX625
PX76A675	1.5	Alkaline	EPX675	H-C, MR44	KX675	V675PX	RPX675	—	MR44	—	1128MP	MR44	4677, 8900, PX675
7K87	6.0	Alkaline	S39	4LR-61	KJ	4018	867	—	—	—	1412AP	4LR61	Size J

DURACELL ULTRA ALKALINE BATTERIES

DURACELL	Voltage	Type	NEDA Industrial/Consumer	Eveready Industrial/Consumer	Rayovac Industrial/Consumer	Bright Star Consumer
MX1300	1.5	D	13AC13A	EN95/E95	AL-D/813	7520
MX1400	1.5	C	14AC14A	EN93/E93	AL-C/814	7522
MX1500	1.5	AA	15AC15A	EN91/E91	AL-AA/815	7524
MX1604	9.0	9 VOLT	1604AC1604A	EN22/E22	AL-9V/A1604	7590
MX2400	1.5	AAA	24AC24A	EN92/E92	AL-AAA/824	7526

DURACELL COPPERTOP ALKALINE BATTERIES

DURACELL	Voltage	Type	NEDA Industrial/Consumer	Eveready Industrial/Consumer	Rayovac Industrial/Consumer	Bright Star Consumer
MN1300	1.5	D	13AC13A	EN95/E95	AL-D/813	7520
MN1400	1.5	C	14AC14A	EN93/E93	AL-C/814	7522
MN1500	1.5	AA	15AC15A	EN91/E91	AL-AA/815	7524
MN1604	9.0	9 VOLT	1604AC1604A	EN22/E22	AL-9V/A1604	7590
MN2400	1.5	AAA	24AC24A	EN92/E92	AL-AAA/824	7526

DURACELL PHOTO/ELECTRONIC/HOME MEDICAL BATTERIES

DURACELL	Voltage	Eveready	Panasonic	Kodak	Varta	Sanyo	Rayovac	Maxell	Toshiba	AWI	NEDA	IEC	Other
DLCR2	3.0	EL1CR2	CR2	KCR2	—	CR2	RLCR2	—	—	—	5046LC	—	CR2
DLR9V3	3.0	—	CR-V3/18	—	—	—	—	—	—	—	—	—	CR-V3 (LB-91E)
DL13N	3.0	2L76	—	K58L	CR13N	CR13N	—	4LR44	—	—	5098LC	CR1108	GL2-76, LM110
DL123A	3.0	EL123AP	CR123A	K123LA	CR123	CR123A	RL123A	CR123	—	—	5018LC	CR17245	—
DL223A	6.0	EL223AP	CR-P2	K223LA	CRP2	CRP2	RL223A	CRP2	—	—	5224LC	CRP2	—
DL245	6.0	EL2CR5	2CR5M	KL2CR5	2CR5	2CR5	RL2CR5	2CR5	—	—	5232LC	2CR5	—
DL2032	3.0	CR2032	CR2032	KCR2032	CR2032	CR2032	RLCR2032	CR2032	CR2032	L14	5094LC	CR2032	EA-2032C
DL2430	3.0	CR2430	CR2430	—	CR2430	CR2430	—	—	—	—	CR2430	L20	5011LC
DL2450	3.0	CR2450	—	—	CR2450	CR2450	—	—	—	—	CR2450	—	5029LC
PX28L	6.0	L544	—	K28L	V28PXL	2CR13N	—	—	—	—	1406LC	2CR1108	4G1317H34

DURACELL PHOTO/ELECTRONIC/HOME MEDICAL BATTERIES

DURACELL	Voltage	Eveready	Panasonic	Kodak	Varta	Sanyo	Rayovac	Maxell	Toshiba	AWI	NEDA	IEC	Other
DL1616	3.0	CR1616	CR1616	—	—	—	—	CR1616	CR1616	—	5221LC	CR1616	—
DL1620	3.0	CR1620	CR1620	—	CR1620	CR1620	—	—	—	L98	5098LC	CR1620	—
DL2016	3.0	CR2016	CR2016	KCR2016	CR2016	CR2016	—	CR2016	CR2016	L10	5093LC	CR2016	TYPE FA EA-50C7/3D
DLR2025	3.0	CR2025	CR2025	KCR2025	CR2025	CR2025	—	CR2025	CR2025	L12	5093LC	CR2025	EA-100CF
MN21	12.0	A23	LRV08	K23A	—	—	—	—	—	—	1811A	3LR50	GP23A
MN27	12.0	A27	—	—	—	—	—	—	—	—	—	—	GP27A, B1



DURACELL CAMCORDER BATTERIES

DURACELL	Voltage	Type	Airac Video	Canon	Chinon	Quintus Mathis	Empire Scientific	Energizer	GE	Hitachi	Maxell	Minolta	Nikon	Panasonic	Pentax	Rollei Shedd	Rayovac	RCA	Salt	Sharp	Sony	Sungpak	Zenith	
DR5	7.2	Lithium Ion	—	—	—	—	—	CM9072	—	—	—	—	NP-500	—	—	—	—	—	—	—	GM8001 NP-500 NP-530 NP-F330 NP-F530	—	—	
DR7	3.6	NiMH	—	—	—	—	—	CM6136	—	—	—	—	—	—	—	—	—	—	—	—	—	BT-H21 BT-H21U BT-H22 BT-H22U	—	
DR8	6.0	NiMH	—	—	—	—	EPP-143	CM-2360 CM-2360C CM-1360	—	BM-8P802G VMBP25 VMBP2A VMBP2G VMBP23 VMBP24	—	VBP-400 VBP-401 VBP-410	—	—	PVB1001 PVB1002	—	—	AV-800 88-060 88-120 88150 BV060 EPP143	—	—	—	—	—	
DR10	6.0	NiMH	—	—	—	—	—	CC2460 CC2460C CCM1460 CCM2460 CCM2460C CCM4060 CCM4060A CCM4060AC CCM4060C CCM5060 CM1160 CM2072 CM2160 CM2160C CM2560 CM2560C CM4160 DY3112C EBNV70U ENP55 ENP56 ENP77	AV-606	—	—	—	—	—	—	—	—	AV-606	—	—	—	AV825 BT-77 BT-77(U) BT-80 BT-80-BK P8100	—	
DR11	6.0	NiMH	AZ602LD	—	C8-B36 C8-B36-1 C8-B36-2	KB00005	—	CC2460 CC2460C CCM1460 CCM2460 CCM2460C CCM4060 CCM4060A CCM4060AC CCM4060C CCM5060 CM1160 CM2072 CM2160 CM2160C CM2560 CM2560C CM4160 DY3112C EBNV70U ENP55 ENP56 ENP77	—	—	—	—	HHR-V40	—	23-215	—	—	—	RC8031	—	BT-BH70(U)	—	—	VAC-560 VAC-914
DR12	6.0	NiMH	—	BP-711 BP-729 BP-918 BP-E711 BP-E714 BP-E722 BP-E729	—	—	EPP-118	CM-1060H CM1060 CM1060C CM1060HC EBPE71 EBPE72	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	RB-10 SV10
DR0915	7.2	Lithium Ion	—	BP-911 BP-911K BP-914 BP-915 BP-915L	—	—	—	ER-C560	—	—	M7220	—	—	—	—	—	—	—	—	—	—	—	—	
DRSM50	7.2	Lithium Ion	—	—	—	—	—	ER-C545	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
DRSM70	7.2	Lithium Ion	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	



DURACELL WATCH BATTERIES

DURACELL	Voltage	Type	Eveready	Rayovac	Timex	Bulova	Saiko	Mazell	Varta	Renata	Panasonic	Toshiba	JIS	ANSI	IEC	AWI	NEDA	
D281386	1.5	Silver Oxide	301	301	D	226	SR433W	SR433W	V201	1	SP301	SR433W	GS12	WS10	SR43	SR4	1132SD	
D281386	1.5	Silver Oxide	306	306	H	280	SR43W	SR43W	V386	6	SP386	SR43W	G12	WS10	SR43	SR7	1132SD	
D303357	1.5	Silver Oxide	303	303	A	—	SR445W	SR445W	V303	9	SP303	SR445W	GS14	WS16	SR47	SR6	1132SD	
D303357	1.5	Silver Oxide	357	357	J	228	SR44W	SR44W	V357	7	SP357	SR44W	G13	WS15	SR44	SR5	1131SD	
D309393	1.5	Silver Oxide	309	309	F	707	—	SR754W	V309	16	WS-6	SR754S.LO	GS5	WS6	SR54	S08	1136SD	
D309393	1.5	Silver Oxide	393	393	F	255	SR48	—	V393	15	SP393	SR48	G5	—	SR48	S15	1137SD	
D319	1.5	Silver Oxide	319	319	—	—	SR527SW	—	—	—	—	—	—	—	—	—	—	
D361362	1.5	Silver Oxide	361	361	X	—	SR7R721W	SR721W	V361	46	SP361	SR721W	—	—	SR58	S23	1178SD	
D361362	1.5	Silver Oxide	362	362	S	601	SR7R721SW	SR721SW	V362	19	SP362	SR721SW	—	—	SR720	S12	1158SD	
D364	1.5	Silver Oxide	364	364	T	602	SR7R621SW	SR621SW	V364	31	SP364	SR621SW	—	—	SR60	S14	1178SD	
D370371	1.5	Silver Oxide	370	370	Z	620	SR920W	SR920W	V370	36	SP370	SR920W	—	—	SR69	S21	1188SD	
D370371	1.5	Silver Oxide	371	371	—	605	SR7R920SW	SR920SW	V371	30	SP371	SR920SW	—	—	SR620	S18	1171SD	
D376	1.5	Silver Oxide	376	376	—	—	SR626W	—	—	—	—	—	—	—	—	—	—	
D377	1.5	Silver Oxide	377	377	BA	606	SR626SW	SR626SW	V377	37	SP377	SR626SW	—	—	SR66	S32	1176SD	
D379	1.5	Silver Oxide	379	379	—	618	SR7R521SW	SR521SW	V379	50	SP379	SR521SW	—	—	—	—	—	
D381391	1.5	Silver Oxide	381	381	—	317	TR1120SW	SR1120SW	V381	34	—	SR1120SW	G58	—	—	—	S20	1176SD
D381391	1.5	Silver Oxide	391	391	L	609	TR1120W	SR1120W	V391	23	SP391	SR1120W	G8	—	SR55	S11	1166SD	
D384382	1.5	Silver Oxide	384	384	—	247	TR41SW	SR41SW	V384	10	SP384	SR41SW	G53	—	—	—	S22	1154SD
D384382	1.5	Silver Oxide	392	392	K	2478	TR41W	SR41W	V392	2	SP392	SR41W	G3	WS4	SR41	S13	1135SD	
D389390	1.5	Silver Oxide	389	389	M	—	SR1130W	SR1130W	V389	17	SP389	SR1130W	G10	—	SR54	S09	1138SD	
D389390	1.5	Silver Oxide	390	390	—	603	SR1130SW	SR1130SW	V390-10	11	SP390	SR1130SW	—	—	—	—	S24	1159SD
D395399	1.5	Silver Oxide	395	395	LA	610	TR927SW	SR927SW	V395	25	SP395	SR927SW	—	—	SR57	S28	1162SD	
D395399	1.5	Silver Oxide	399	399	W	613	TR927W	SR927W	V399	35	SP399	SR927W	—	—	SR57	S19	1165SD	
D396397	1.5	Silver Oxide	396	396	V	612	TR726W	SR726W	V396	29	SP396	SR726W	—	—	SR59	S17	1163SD	
D396397	1.5	Silver Oxide	397	397	N	607	SR726SW	SR726SW	V397	26	SP397	SR726SW	—	—	—	—	S30	1164SD
DL1025	3.0	Lithium	CR1025	CR1025	—	—	—	—	—	—	—	—	—	—	—	—	—	
DL1216	3.0	Lithium	CR1216	CR1216	—	—	—	—	—	—	—	—	—	—	—	—	—	

DURACELL HEARING AID BATTERIES

DURACELL	Voltage	Type	Eveready	Rayovac	Miracle Ear	Panasonic	Varta	NEDA	IEC	Other
D410	1.4	Zinc Air	AC230, AC10	L102A, 10A	ME10Z	PR-10PA	V10AT	7003ZD	PR10PPR36	B209A, S10A, ZA10, 105A
D413	1.4	Zinc Air	AC13	L132A, 13A	ME8Z	PR-13PA	V13AT	7000ZD	PR48	B269A, S13A, ZA13, 135A
D4312	1.4	Zinc Air	AC312	L3122A, 312A	ME7Z	PR-312PA	V312AT	7022ZD	PR41	B347PA, S312A, ZA312, 3125A
D4675	1.4	Zinc Air	AC675	L6752A, 675A	ME9Z	PR-675PA	V675AT	7003ZD	PR44	B900PA, S675A, ZA675, 6755A

DURACELL ALKALINE LANTERN BATTERIES

DURACELL	Voltage	Type	Eveready	Rayovac	NEDA	IEC
MN908	6.0	Alkaline	529	—	908A	4LR25X
MN918	6.0	Alkaline	521	—	918A	4LR25-2
MN1203	4.5	Alkaline	—	—	—	—

MALLORY SUPER BATTERIES

MALLORY	Voltage	Type	Eveready	Panasonic	Mazell	Rayovac	Toshiba	Varta	NEDA	IEC
M13SHD	1.5	D Size	1250	UM11N	SUM1	6D	R20U	2620	13D	R20
M14SHD	1.5	C Size	1235	UM2N	SUM2	4C	R14U	2614	14D	R14
M15SHD	1.5	AA Size	1215	UM3N	SUM3	5AA	R6U	2606	15D	R6
MV9SHD	9.0	9 Volt	1222	00RPN	S006	D1604	6F22U	3022	1604D	6F22