	PRODUCT S	PECIFICATION	[Panasonic			
Individual Product Specification								
Specifica Cylindric R6 (DRC	al Zinc Carb	oon Batte	ry					
Date of stipulation: 2001-03-02	S	tipulated			Described			

PRODUCT SPECIFICATION									Panasonic		
Individual Product Specification										DRC	
1.	Battery iden	tificatio	on			gr.					
2.	2. Battery dimensions As per attached drawing										
3. Typical battery performance Discharge modes											
	Test	st Resista Daily period				End poir	nt	Result *	Result**		
	Radio	43	•		4 h		0.9 V		28 h	24.5 h	
	Recorder	10			1 h		0.9 V		4.0 h	3.3 h	
	Motor	3.9			1 h		0.8 V		1.0 h	0.78 h	
	Pulse	1.8		15 sec	/ min. 24 h		0.9 V		60	50	
Open circuit voltage (OCV) Minimum average duration										-	
OCV (at 20±2 ^o C) Min. aver. duration (at 20±2 ^o C)***				⁰ C)***		1.6 V 22.0 h		1.52 V 19.5 h	_		
 * The initial discharge test shall commence with 30 days since manufacture. During this period, the batteries are kept under the condition of 20±2°C. *** 43 , 4 h / day, 0.9 V 4. Mercury and Cadmium contents No Mercury (Hg) and Cadmium (Cd) are used in battery. 											
Da	ate of stipula 2001-03-0			S	tipulated					Described	